Skip to main content Skip to primar	<u>r navigation</u>	
 <u>Home Home</u> <u>About this portal</u> <u>Latest updates</u> 		
Print Save Email Resource detail Citations		

NZS 3106:2009 Design of concrete structures for the storage of liquids

Table of Contents

<u>View on Information Provider website Download this resource (PDF, 5.1MB)</u> {{ linkText }}

Abbreviation NZS 3106:2009 Valid from 28/07/2009 Replaces <u>NZS 3106:1986</u>

Information provider
Standards New Zealand
Author
Standards New Zealand
Information type
New Zealand Standard
Format
PDF
Cited By
This resource is cited by 13 documents (show Citations)
Cites

This resource cites 5 documents (show Citations)

Description

This Standard provides design information that meets the requirements of the New Zealand Building Code and is intended to be used by engineers and others involved in new storage tank projects. It provides a basis for designing concrete structures for the storage of liquids that will require only limited periodic maintenance to remain serviceable for their design life, and will not allow an uncontrolled, rapid loss of the liquid contents in extreme events such as a major earthquake.

Scope

This Standard is intended to provide a means of compliance with the requirements of the New Zealand Building Code for concrete structures that will store liquid, and would be used regularly by engineers and organisations about to embark on a new storage tank project. The Standard covers: (a) Design requirements and guidance; (b) Loading requirements; and (c) Seismic considerations and allowances.

For assistance with locating previous versions, please contact the information provider.

 Table of Contents
 View on Information Provider website Download this resource (PDF, 5.1MB)
 {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

NZS 3106:2009 Design of concrete structures for the storage of liquids

This document is CITED BY:

• B1/VM1 (First edition, amendment 15)

NZS 3106:2009 is cited by Verification Method B1/VM1: Structure - General from 30/09/2010

• B1/VM1 (First edition, Amendment 14)

NZS 3106:2009 is cited by Verification Method B1/VM1: Structure - General from 30/09/2010

• B1/VM1 (First Edition, Amendment 17)

NZS 3106:2009 is cited by Verification Method B1/VM1: Structure - General from 30/09/2010

• B1/VM1 (First edition, Amendment 10)

NZS 3106:2009 is cited by Verification Method B1/VM1: Structure - General from 30/09/2010

• B1/VM1 (First Edition, Amendment 12.)

NZS 3106:2009 is cited by Verification Method B1/VM1: Structure - General from 30/09/2010

• B1/VM1 (First edition, Amendment 13)

NZS 3106:2009 is cited by Verification Method B1/VM1: Structure - General from 30/09/2010

• B1/VM1 (First edition, Amendment 16)

NZS 3106:2009 is cited by Verification Method B1/VM1: Structure - General from 30/09/2010

• B1/VM1 (First Edition, Amendment 11)

NZS 3106:2009 is cited by Verification Method B1/VM1: Structure - General from 30/09/2010

• B1/VM1 (First Edition, Amendment 18)

NZS 3106:2009 is cited by Verification Method B1/VM1: Structure - General from 30/09/2010

• G14/VM1 (Second Edition, Amendment 5)

NZS 3106:2009 is cited by Verification Method G14/VM1: Industrial Liquid Waste from 30/09/2010

• G14/VM1 (Second Edition, Amendment 6)

NZS 3106:2009 is cited by Verification Method G14/VM1: Industrial Liquid Waste from 30/09/2010

<u>G14/VM1 (Second Edition, Amendment 4)</u>

NZS 3106:2009 is cited by Verification Method G14/VM1: Industrial Liquid Waste from 30/09/2010

• G14/VM1 (Second Edition, Amendment 3)

NZS 3106:2009 is cited by Verification Method G14/VM1: Industrial Liquid Waste from 30/09/2010

Back

NZS 3106:2009 Design of concrete structures for the storage of liquids

Show what documents this resource is CITED BY Show what documents this resource CITES

Description

This Standard provides design information that meets the requirements of the New Zealand Building Code and is intended to be used by engineers and others involved in new storage tank projects. It provides a basis for designing concrete structures for the storage of liquids that will require only limited periodic maintenance to remain serviceable for their design life, and will not allow an uncontrolled, rapid loss of the liquid contents in extreme events such as a major earthquake.

View on Information Provider website Download this resource (PDF, 5.1MB)

NZS 3106:2009 Design of concrete structures for the storage of liquids

Description

This Standard provides design information that meets the requirements of the New Zealand Building Code and is intended to be used by engineers and others involved in new storage tank projects. It provides a basis for designing concrete structures for the storage of liquids that will require only limited periodic maintenance to remain serviceable for their design life, and will not allow an uncontrolled, rapid loss of the liquid contents in extreme events such as a major earthquake.

View on Information Provider website Download this resource (PDF, 5.1MB)

This resource cites:

NZS 3106:2009 Design of concrete structures for the storage of liquids

This document CITES:

New Zealand Standards

• <u>AS/NZS 1170.0:2002</u>

NZS 3106:2009 cites AS/NZS 1170.0:2002 Structural Design Actions - General principles

• AS/NZS 1170.1:2002

NZS 3106:2009 cites AS/NZS 1170.1:2002 (R2016) Structural Design Actions - Permanent, imposed and other actions

• NZS 1170.5:2004

NZS 3106:2009 cites NZS 1170.5:2004 Structural Design Actions - Part 5: Earthquake design actions - New Zealand

• NZS 3101.1&2:2006

NZS 3106:2009 cites NZS 3101.1&2:2006 Concrete structures standard. The design of concrete structures

• <u>NZS 3109:1997</u>

NZS 3106:2009 cites NZS 3109:1997 Concrete construction

Back

Close

Table of Contents

1 General

1.1 Scope

1.2 New Zealand Building Legislation

1.3 Interpretation

- **1.4 Appendices**
- **1.5 Design And Construction**
- **2 Definitions And Abbreviations**
- 2.1 Definitions
- 2.2 Abbreviations
- 2.3 Notation
- **3 General Design Requirements**
- 3.1 Design Methods
- 3.2 Support Structures
- 3.3 Tanks Storing Portable Water
- 3.4 Pipework
- 3.5 Freeboard
- 4 Loads And Load Combinations
- 4.1 General
- 4.2 Loads And Other Actions
- 4.3 Load Control
- 4.4 Non-Symmetric Loads For Circular Tank
- 4.5 Load Combinations For Serviceability Limit State
- 4.6 Load Combinations For Ultimate Limit State
- **5 Design For Serviceability**
- 5.1 General Considerations
- 5.2 Reinforced Concrete
- **5.3 Prestressed Concrete**
- 6 Design For Strength And Stability At The Ultimate Limit State
- 6.1 General

6.2 Stability Design

- **6.4 Minimum Reinforcement**
- 7 Design For Durability

Appendix

- A Earthquake Actions
- **B** Design Of Reinforcement To Control Cracking

C – Testing

D – Thermal Stress Coefficients

Table

- 1 Roof Temperature Criteria
- 2 Moisture Variation Shrinkage And Swelling Strains

3 – Liquid Tightness Class And Leakage Control Provisions For Group A Loads

4 – Reinforcement Ratio For Fully Restrained Concrete

5 – Limiting Stresses In Steel Reinforcement Where Compression Zone Depth Complies With 5.1.1

6 – Limiting Stresses In Steel Reinforcement Where Compression Zone Depth Is Less Than 5.1.1

- 7 Limiting Stresses In Prestressed Concrete
- 8 Exposure Classifications
- A1 Displacement Ductility Factor, M
- A2 Correction Factor Kf (M, Ei)
- **B1 Ratio Of Bond Strength**
- **B2 Strength And Deformation Characteristics For Concrete**
- D1 Thermal Stress Coefficients Pinned-Base Condition
- **D2 Thermal Stress Coefficients Fixed-Base Condition**
- D3 Thermal Stress Coefficients Sliding-Base Condition

Figure

- 1 Temperature Distributions In Tank Walls
- 2 Effective Concrete Area

3 – Reduction Of Stiffness Of Doubly Reinforced Wall On Cracking (Includingtension Stiffening Effect)

- A1 Damping For Horizontal Impulsive Mode
- A2 Damping For Vertical Impulsive Mode
- A3 Dimensionless Period For Fundamental Sloshing Model

A4 – Equivalent Weights Of Impulsive And Convective Contents (Circularand Rectangular Tanks)

- A5 Equivalent Weight Distribution
- A6 Horizontal Force Distribution

A7 – Equivalent Heights Of Impulsive And Convective Weights For Overturning (Circular And Rectangular Tanks)

- A8 Approximate Method For Estimating Buoyancy Pressure On Roof
- B1 Effective Tension Area
- B2 Crack Width, W, At Concrete Surface Relative To Distance From Bar
- **D1 Differential Temperature Change**

D2 – Total Temperature Change

Print Save Email		
Feedback	 	
 <u>Contact us</u> <u>Privacy policy</u> <u>Disclaimer</u> <u>Copyright</u> 		
Feedback		