

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Resource detail](#)
[Citations](#)

AS/NZS 3750.11:2009 Paints for steel structures - Chlorinated rubber - High-build and gloss

[View on Information Provider website](#)

Abbreviation

AS/NZS 3750.11:2009

Valid from

19/04/2009

Information provider

Standards New Zealand

Author

Standards New Zealand, Standards Australia

Information type

New Zealand Standard

Format

PDF

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This part of AS/NZS 3750 specifies requirements for a high-build, chlorinated rubber based, intermediate or topcoat paint and a chlorinated rubber gloss finish paint for the protection of iron and steel against exterior atmospheric corrosion in an industrial or marine environment.

The high-build paints are suitable for application only by conventional air or airless spraying, while the gloss paint is suitable for application by brush or spray. Paints specified in this Standard are described in AS/NZS 2312 as Paint References C14 and C25.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS/NZS 3750.11:2009 Paints for steel structures - Chlorinated rubber - High-build and gloss

This document is CITED BY:

- [AS/NZS 5131:2016](#)

AS/NZS 3750.11:2009 is cited by AS/NZS 5131:2016 Structural steelwork - Fabrication and erection

Back

AS/NZS 3750.11:2009 Paints for steel structures - Chlorinated rubber - High-build and gloss

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This part of AS/NZS 3750 specifies requirements for a high-build, chlorinated rubber based, intermediate or topcoat paint and a chlorinated rubber gloss finish paint for the protection of iron and steel against exterior atmospheric corrosion in an industrial or marine environment.

The high-build paints are suitable for application only by conventional air or airless spraying, while the gloss paint is suitable for application by brush or spray. Paints specified in this Standard are described in AS/NZS 2312 as Paint References C14 and C25.

[View on Information Provider website](#)

[AS/NZS 3750.11:2009 Paints for steel structures - Chlorinated rubber - High-build and gloss](#)

Description

This part of AS/NZS 3750 specifies requirements for a high-build, chlorinated rubber based, intermediate or topcoat paint and a chlorinated rubber gloss finish paint for the protection of iron and steel against exterior atmospheric corrosion in an industrial or marine environment.

The high-build paints are suitable for application only by conventional air or airless spraying, while the gloss paint is suitable for application by brush or spray. Paints specified in this Standard are described in AS/NZS 2312 as Paint References C14 and C25.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS/NZS 3750.11:2009 Paints for steel structures - Chlorinated rubber - High-build and gloss

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)

- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)