

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

AS/NZS 3750.1:2008 Paints for steel structures - Epoxy mastic (two-pack) - For rusted steel

[View on Information Provider website](#)

Abbreviation

AS/NZS 3750.1:2008

Valid from

18/05/2008

Information provider

Standards New Zealand

Author

Standards New Zealand, Standards Australia

Information type

New Zealand Standard

Format

PDF

Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

Description

This part of AS/NZS 3750 specifies requirements for a two-component, high-build, high-solids, epoxy mastic for the protection of iron and steel against exterior atmospheric corrosion in a severe industrial or coastal marine environment.

Provides requirements for two-component, high-build, high solids, epoxy mastic paint for the protection of iron and steel against exterior atmospheric corrosion.

Scope

It is intended primarily for use on imperfectly prepared surfaces, i.e. surfaces which have been cleaned only by hand or power tool to the extent that bare steel areas with residual rust and some previously applied paint of any type are still present.

NOTES:

1. This paint may be used as detailed for system SP3, MP8A in AS 2312.
2. Appendix A contains recommendations and advice on information which should be provided by the purchaser at the time of enquiry or order.
3. Additional information on the use and application of epoxy paints is contained in Appendix B.
4. Alternative methods for determining compliance with this Standard are given in Appendix C.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS/NZS 3750.1:2008 Paints for steel structures - Epoxy mastic (two-pack) - For rusted steel

This document is CITED BY:

- [AS/NZS 2699.3:2002](#)

AS/NZS 3750.1:2008 is cited by AS/NZS 2699.3:2002 Built-in components for masonry construction - Lintels and shelf angles (durability requirements)

- [AS/NZS 5131:2016](#)

AS/NZS 3750.1:2008 is cited by AS/NZS 5131:2016 Structural steelwork - Fabrication and erection

AS/NZS 3750.1:2008 Paints for steel structures - Epoxy mastic (two-pack) - For rusted steel

Description

This part of AS/NZS 3750 specifies requirements for a two-component, high-build, high-solids, epoxy mastic for the protection of iron and steel against exterior atmospheric corrosion in a severe industrial or coastal marine environment.

Provides requirements for two-component, high-build, high solids, epoxy mastic paint for the protection of iron and steel against exterior atmospheric corrosion.

[View on Information Provider website](#)

[AS/NZS 3750.1:2008 Paints for steel structures - Epoxy mastic \(two-pack\) - For rusted steel](#)

Description

This part of AS/NZS 3750 specifies requirements for a two-component, high-build, high-solids, epoxy mastic for the protection of iron and steel against exterior atmospheric corrosion in a severe industrial or coastal marine environment.

Provides requirements for two-component, high-build, high solids, epoxy mastic paint for the protection of iron and steel against exterior atmospheric corrosion.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS/NZS 3750.1:2008 Paints for steel structures - Epoxy mastic (two-pack) - For rusted steel

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print

[Save](#)

Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

--	--	--

--

[Feedback](#)