Skip to main content Skip to primary navigation Menu						
 Home Home About this portal Latest updates 						
Print Save Email Resource detail Citations						
NZS 4218:2004 Energy efficiency - Small building envelope Table of Contents View on Information Provider website Download this resource (PDF, 1.6MB) {{ linkText }}						
Abbreviation NZS 4218:2004 Valid from 30/08/2004	{{ mikrext }}					
Replaces NZS 4218:1996						
Information provider Standards New Zealand						
Author						
Standards New Zealand						
Information type New Zealand Standard						
Format						

Cited By

PDF

This resource is cited by 5 documents (show Citations)

Description

This Standard specifies thermal insulation requirements for housing and small buildings to achieve an adequate level of energy efficiency.

Scope

Provides details and guidance to meet adequate energy efficiency performance requirements for the building envelope of housing and small buildings.

Incorporates glazing into the schedule and calculation methods of compliance with the required performance and focuses on excessive heat-loss through the area of glazing.

It also brings the window R-values into line with Window Efficiency Rating Scheme (WERS) and adds an Appendix on glazing performance.

It focuses on areas of glazing above 30% of the total wall area as these significantly affect thermal efficiency of the envelope.

 $\label{prop:control} \mbox{For assistance with locating previous versions, please contact the information provider.}$

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

NZS 4218:2004 Energy efficiency - Small building envelope

This document is CITED BY:

• H1/AS1 (Third Edition, Amendment 2)

NZS 4218:2004 is cited by Acceptable Solution H1/AS1: Energy Efficiency from 31/10/2007

H1/AS1 (Third Edition (unamended))

NZS 4218:2004 is cited by Acceptable Solution H1/AS1: Energy Efficiency from 31/10/2007

H1/VM1 (Third Edition, Amendment 2)

NZS 4218:2004 is cited by Verification Method H1/VM1: Energy Efficiency from 31/10/2007

• H1/VM1 (Third Edition (unamended))

NZS 4218:2004 is cited by Verification Method H1/VM1: Energy Efficiency from 31/10/2007

NZS 4214:2006

NZS 4218:2004 is cited by NZS 4214:2006 Methods of determining the total thermal resistance of parts of buildings

Back

NZS 4218:2004 Energy efficiency - Small building envelope

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard specifies thermal insulation requirements for housing and small buildings to achieve an adequate level of energy efficiency.

View on Information Provider website Download this resource (PDF, 1.6MB)

NZS 4218:2004 Energy efficiency - Small building envelope

Description

This Standard specifies thermal insulation requirements for housing and small buildings to achieve an adequate level of energy efficiency.

View on Information Provider website Download this resource (PDF, 1.6MB)

This resource does not cite any other resources.

NZS 4218:2004 Energy efficiency - Small building envelope

This resource does not CITE any other resources.



Close

Table of Contents
1 General
1.1 Scope
1.2 Definitions
1.3 Purpose And Context Of Use
2 General Requirements
2.1 Groups Of Buildings
2.2 Integrity Of Thermal Insulation
2.3 Conservatories, Outbuildings And Atria
3 Compliance Methods
3.1 Schedule Method
3.2 Calculation Method
3.3 Modelling Method
Appendices
Appendix A Modelling Method – Building Energy Use Comparison
A1 Modelling Requirements
A2 Thermal Envelope
A3 Lighting
A4 Internal Loads
A5 Conditioning System Modelling
A6 Reference Building
A7 Information And Documentation
Appendix B Climate Zones
Appendix C Heat Loss Equation Tables

Appendix D Worked Example

Appendix F Measurement Details

Appendix E Building Component R-Value Combinations

Appendix G Glazing And The Window Efficiency Rating Scheme (Wers)

Appendix H Orientation

Tables

Table 1 – Non-Solid Construction – Minimum R-Values For Schedule Method (Only Where Area Of Glazing Is 30 % Or Less Of Total Wall Area)

Table 2 – Solid Construction – Alternative Minimum R-Values For Schedule Method (Only Where Area Of Glazing Is 30 % Or Less Of Total Wall Area)

Table 3 – Heated Walls, Ceilings Or Floors – Minimum R-Values For Schedule Method

Table 4 – Reference Building – Area Of Glazing R-Values

Table A1 – Default Power Densities For Internal Gains From Occupants And Plug Loads

Table A2 – Default Schedules For Occupancy And Plug Loads – Percentage Of Maximum Load Or Percentage Of Power Density

Table C1 – Reference Heat Loss Equations – Non-Solid Construction

Table C2 – Reference Heat Loss Equations – Solid Construction

Table E1 – Building Component R-Value Combinations

Table G1 – Climate Zones 1 And 2: Wers Star Rating

Table G2 - Climate Zone 3: Wers Star Rating

Figures

Figure 1 – Decision Flowchart

Figure B1 – Climate Zones

Figure F1 – Floor And Wall Area Measurements And R-Value Locations

Figure F2 – Roof Area Measurements

Figure F3 – Roof Area Measurements

Figure F4 – Total Wall Area

Figure F5 – Wall Area

- Figure F6 Window Measurement Single Window
- Figure F7 Bow Or Bay Window Measurement
- Figure F8 Rooflight Measurement
- Figure F9 Skylight Measurement
- Figure H1 Orientation Sectors

Print Save Email		
<u>Feedback</u>		
		_
 Contact us 		
 Privacy policy 		
• <u>Disclaimer</u>		
 Copyright 		
	<u>u</u>	<u> </u>

Feedback