

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

NZS 4223.4:2008 Code of practice for glazing in buildings - Wind, dead, snow, and live actions

Table of Contents

[View on Information Provider website](#) `{{ linkText }}`

Abbreviation

NZS 4223.4:2008

Amendment

Amendment 1 - incorporated. Published 29/02/2016.

Valid from

28/05/2008

Replaces

Information provider

Standards New Zealand

Author

Standards New Zealand

Information type

New Zealand Standard

Format

PDF

Cited By

[This resource is cited by 13 documents \(show Citations\)](#)

Cites

[This resource cites 15 documents \(show Citations\)](#)

Description

NZS 4223.4 provides a method for the determination of minimum glass thickness for vertical and sloped overhead glazing in New Zealand to resist limit state actions.

Scope

The following are excluded from the scope of NZS 4223 Parts 1, 2, 3, and 4:

- (a) Glazing in lift cars and liftwells (refer to NZS 4223.1, Appendix A for guidance);
- (b) Furniture glass, cabinet glass, vanities, glass basins, refrigeration units, internal glass fitments and glass wall linings, framed internal wall mirrors, and mirrors not specifically covered by these parts;
- (c) Buildings and structures with no public access intended for non-habitable building structures for horticultural or agricultural use;
- (d) Restoration or repairs to existing decorated glass;
- (e) Glazing applications that might fail due to stresses other than tensile stresses, such as glass floors;
- (f) Plastic glazing materials;
- (g) The construction and installation of windows (refer to NZS 3504, NZS 3619, and NZS 4232.2);
- (h) Glass blocks, pavers, slumped, formed, or cast glass;
- (i) Point-fixed or point-supported systems, used for glazing, cladding, signage, and the like, not specifically covered by these parts (refer to Part 1 for design criteria and guidance for specific design).

For assistance with locating previous versions, please contact the information provider.

[Table of Contents](#) [View on Information Provider website](#) `{{ linkText }}`

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

NZS 4223.4:2008 Code of practice for glazing in buildings - Wind, dead, snow, and live actions

This document is CITED BY:

- [B1/AS1 \(First edition, amendment 15\)](#)

NZS 4223.4:2008 is cited by Acceptable Solution B1/AS1: General from 30/09/2010

- [B1/AS1 \(First edition, Amendment 12\)](#)

NZS 4223.4:2008 is cited by Acceptable Solution B1/AS1: General from 30/09/2010

- [B1/AS1 \(First edition, Amendment 16\)](#)

NZS 4223.4:2008 is cited by Acceptable Solution B1/AS1: General from 30/09/2010

- [B1/AS1 \(First edition, Amendment 14\)](#)

NZS 4223.4:2008 is cited by Acceptable Solution B1/AS1: General from 30/09/2010

- [B1/AS1 \(First edition, Amendment 11\)](#)

NZS 4223.4:2008 is cited by Acceptable Solution B1/AS1: General from 30/09/2010

- [B1/AS1 \(First Edition, Amendment 17\)](#)

NZS 4223.4:2008 is cited by Acceptable Solution B1/AS1: General from 30/09/2010

- [B1/AS1 \(First edition, Amendment 13\)](#)

NZS 4223.4:2008 is cited by Acceptable Solution B1/AS1: General from 30/09/2010

- [B1/AS1 \(First edition, Amendment 10\)](#)

NZS 4223.4:2008 is cited by Acceptable Solution B1/AS1: General from 30/09/2010

- [SH/AS1 \(First edition, unamended\)](#)

NZS 4223.4:2008 is cited by SH/AS1 Simple House Acceptable Solution

- [NZS 4211:2008](#)

NZS 4223.4:2008 is cited by NZS 4211:2008 Specification for performance of windows

- [NZS 4223.1:2008](#)

NZS 4223.4:2008 is cited by NZS 4223.1:2008 Code of practice for glazing in buildings - Glass selection and glazing

- [NZS 4223.2:2016](#)

NZS 4223.4:2008 is cited by NZS 4223.2:2016 Glazing in buildings Part 2: Insulating glass units

- [NZS 4223.3: 2016](#)

NZS 4223.4:2008 is cited by NZS 4223.3: 2016 Glazing in buildings - Human impact safety requirements

Back

NZS 4223.4:2008 Code of practice for glazing in buildings - Wind, dead, snow, and live actions

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

NZS 4223.4 provides a method for the determination of minimum glass thickness for vertical and sloped overhead glazing in New Zealand to resist limit state actions.

[View on Information Provider website](#)

[NZS 4223.4:2008 Code of practice for glazing in buildings - Wind, dead, snow, and live actions](#)

Description

NZS 4223.4 provides a method for the determination of minimum glass thickness for vertical and sloped overhead glazing in New Zealand to resist limit state actions.

[View on Information Provider website](#)

This resource cites:

NZS 4223.4:2008 Code of practice for glazing in buildings - Wind, dead, snow, and live actions

This document CITES:

New Zealand Standards

- [AS/NZS 1170.0:2002](#)

NZS 4223.4:2008 cites AS/NZS 1170.0:2002 Structural Design Actions - General principles

- [AS/NZS 1170.1:2002](#)

NZS 4223.4:2008 cites AS/NZS 1170.1:2002 Structural Design Actions - Permanent, imposed and other actions

- [AS/NZS 1170.2:2002](#)

NZS 4223.4:2008 cites AS/NZS 1170.2:2002 Structural Design Actions - Wind Actions

- [AS/NZS 1170.3:2003](#)

NZS 4223.4:2008 cites AS/NZS 1170.3:2003 Structural Design Actions - Snow and ice actions

- [AS/NZS 4667:2000](#)

NZS 4223.4:2008 cites AS/NZS 4667:2000 Quality requirements for cut-to-size and processed glass

- [NZS 3504:1979](#)

NZS 4223.4:2008 cites NZS 3504:1979 Specification for aluminium windows

- [NZS 3604:1999](#)

NZS 4223.4:2008 cites NZS 3604:1999 Timber framed buildings

- [NZS 3619:1979](#)

NZS 4223.4:2008 cites NZS 3619:1979 Specification for timber windows

- [NZS 4223 Supplement 1:2008](#)

NZS 4223.4:2008 cites NZS 4223 Supplement 1:2008 Code of practice for glazing in buildings - Supplement 1 to NZS 4223.1:2008 and NZS 4223.4:2008

- [NZS 4223.1:2008](#)

NZS 4223.4:2008 cites NZS 4223.1:2008 Code of practice for glazing in buildings - Glass selection and glazing

- [NZS 4223.2:2016](#)

NZS 4223.4:2008 cites NZS 4223.2:2016 Glazing in buildings Part 2: Insulating glass units

- [NZS 4223.3: 2016](#)

NZS 4223.4:2008 cites NZS 4223.3: 2016 Glazing in buildings - Human impact safety requirements

- [NZS 4229:1999](#)

NZS 4223.4:2008 cites NZS 4229:1999 Concrete masonry buildings not requiring specific engineering design

- [NZS 4232.2:1988](#)

NZS 4223.4:2008 cites NZS 4232.2:1988 Performance criteria for fire resisting enclosures - Fire resisting glazing systems

Australian Standards

- [AS 1288:2006 \(R2016\)](#)

NZS 4223.4:2008 cites AS 1288:2006 (R2016) Glass in buildings

Back

Close

Table of Contents

1 Scope And General

1.1 Scope

1.2 Application

1.3 Compliance With Nzbc

1.4 Interpretation

1.5 Definitions

2 Vertical Glazing

2.1 General

2.2 Design Wind Pressure

2.3 Insulating Glass Units

2.4 Maximum Span For Glass Panels Subjected To Wind Actions

2.5 Organic Safety Lms And Other Glass Coatings

3 Sloped Glazing

3.1 General

3.2 Design Criteria

3.3 Loads And Actions

3.4 Selection Of Sloped Overhead Glass

Appendix

A Simplified Method For Determining Ultimate And Serviceability Limit State Design Wind Pressures

B Calculation Examples

C Sloped Overhead Glazing Fracture Characterustis

D Sloped Glazing – Insulation Glass Units

E Method For The Determination Of The Wind Pressure On Sloped Glazing

F Maximum Spans For 1.1 Kn Live Loadsoads

Table

1 – Wind Pressures For Nzs 3604 And Nzs 4229 Structures

2 – Glass Thickness

3 – Glass Type Factor C1

4 – Serviceability Limit State Wind Pressures

5 – Loads Perpendicular To The Glass Due To Self (Dead) Weight And Snow

6 – Maximum Altitudes (M) For The Application Of 0.5 Kpa And 1.0 Kpa Snow Loads Foreach Snow Zone

7 – Maximum Span Of Annealed Laminated Glass

8 – Maximum Span Of Heat-Strengthened Laminated Glass

9 – Maximum Span Of Toughened Laminated Glass

10 – Maximum Span Of Monolithic Toughened Glass

11 – Building Limitations Applicable To Table 12

12 – Ultimate And Serviceability Limit State Design Wind Pressures For Glazing In Walls Ofbuildings With Limitations As Detailed In Table 11

13 – Basic Ultimate Limit State (Uls) Wind Pressure (Kpa) For Sloped Glazing For Atland Areas

14 – Basic Ultimate Limit State (Uls) Wind Pressure (Kpa) For Sloped Glazing For Areasother Than At Land Areas

15 – Ultimate Limit State (Uls) Design Wind Pressures For Sloping Glass In Buildings (Kpa)

16 – Maximum Span Of Laminated Annealed Glass

17 – Maximum Span Of Laminated Heat-Strengthened Glass

18 – Maximum Span Of Laminated Toughened Glass

19 – Maximum Span Of Toughened Glass

Figure

1 – Maximum Span For Monolithic 3 Mm Annealed Glass

2 – Maximum Span For Monolithic 4 Mm Annealed Glass

3 – Maximum Span For Monolithic 5 Mm Annealed Glass

4 – Maximum Span For Monolithic 6 Mm Annealed Glass

5 – Maximum Span For Monolithic 8 Mm Annealed Glass

6 – Maximum Span For Monolithic 10 Mm Annealed Glass

7 – Maximum Span For Monolithic 12 Mm Annealed Glass

8 – Maximum Span For Monolithic 15 Mm Annealed Glass

9 – Maximum Span For Monolithic 19 Mm Annealed Glass

10 – Maximum Span For Monolithic 25 Mm Annealed Glass

- 11 – Maximum Span For Monolithic 4 Mm Toughened Glass**
- 12 – Maximum Span For Monolithic 5 Mm Toughened Glass**
- 13 – Maximum Span For Monolithic 6 Mm Toughened Glass**
- 14 – Maximum Span For Monolithic 8 Mm Toughened Glass**
- 15 – Maximum Span For Monolithic 10 Mm Toughened Glass**
- 16 – Maximum Span For Monolithic 12 Mm Toughened Glass**
- 17 – Maximum Span For Monolithic 15 Mm Toughened Glass**
- 18 – Maximum Span For Monolithic 19 Mm Toughened Glass**
- 19 – Maximum Span For Monolithic 25 Mm Toughened Glass**
- 20 – Maximum Span For Monolithic 3 Mm Heat-Strengthened Glass**
- 21 – Maximum Span For Monolithic 4 Mm Heat-Strengthened Glass**
- 22 – Maximum Span For Monolithic 5 Mm Heat-Strengthened Glass**
- 23 – Maximum Span For Monolithic 6 Mm Heat-Strengthened Glass**
- 24 – Maximum Span For Monolithic 8 Mm Heat-Strengthened Glass**
- 25 – Maximum Span For Monolithic 10 Mm Heat-Strengthened Glass**
- 26 – Maximum Span For Monolithic 12 Mm Heat-Strengthened**

Glass

27 – Maximum Span For 5 Mm Annealed Laminated Glass

28 – Maximum Span For 6 Mm Annealed Laminated Glass

29 – Maximum Span For 8 Mm Annealed Laminated Glass

30 – Maximum Span For 10 Mm Annealed Laminated Glass

31 – Maximum Span For 12 Mm Annealed Laminated Glass

32 – Maximum Span For 16 Mm Annealed Laminated Glass

33 – Maximum Span For 20 Mm Annealed Laminated Glass

34 – Maximum Span For 24 Mm Annealed Laminated Glass

35 – Curves For B/T Allowable For De Ection Of Glass Limited To Span/60

36 – Snow Zones

B1 – Example Monolithic 4 Mm Toughened Glass

B2 – Example Monolithic 5 Mm Toughened Glass

D1 – Insulating Glass Unit Slope Combinations

E1 – Wind Regions And Lee Zones

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)

- [Copyright](#)

[Feedback](#)