

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

## **NZS 4402.4.1.3:1986 Methods of testing soils for civil engineering purposes - Part 4: Soil compaction tests - Determination of the dry density/water content relationship - Test 4.1.3 New Zealand vibrating hammer compaction test**

[View on Information Provider website](#)

Abbreviation

NZS 4402.4.1.3:1986

Valid from

31/12/1985

---

Information provider

Standards New Zealand

Author

Standards New Zealand

Information type

New Zealand Standard

Format

PDF

---

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

**Description**

Covers the determination of the dry density when the soil passing a 37.5 mm test sieve is compacted by an electrically operated vibrating hammer compactor, over a range of water contents, including that which gives the maximum dry density. To be read in conjunction with Part 1 of this

Standard series.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## **NZS 4402.4.1.3:1986 Methods of testing soils for civil engineering purposes - Part 4: Soil compaction tests - Determination of the dry density/water content relationship - Test 4.1.3 New Zealand vibrating hammer compaction test**

This document is CITED BY:

- [NZS 4431:1989](#)

NZS 4402.4.1.3:1986 is cited by NZS 4431:1989 Code of practice for earth fill for residential development

Back

## **NZS 4402.4.1.3:1986 Methods of testing soils for civil engineering purposes - Part 4: Soil compaction tests - Determination of the dry density/water content relationship - Test 4.1.3 New Zealand vibrating hammer compaction test**

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

Covers the determination of the dry density when the soil passing a 37.5 mm test sieve is compacted by an electrically operated vibrating hammer compactor, over a range of water contents, including that which gives the maximum dry density. To be read in conjunction with Part 1 of this Standard series.

[View on Information Provider website](#)

[NZS 4402.4.1.3:1986 Methods of testing soils for civil engineering purposes - Part 4: Soil compaction tests -](#)

[Determination of the dry density/water content relationship - Test 4.1.3 New Zealand vibrating hammer compaction test](#)

Description

Covers the determination of the dry density when the soil passing a 37.5 mm test sieve is compacted by an electrically operated vibrating hammer compactor, over a range of water contents, including that which gives the maximum dry density. To be read in conjunction with Part 1 of this Standard series.

[View on Information Provider website](#)

This resource does not cite any other resources.

**NZS 4402.4.1.3:1986 Methods of testing soils for civil engineering purposes - Part 4: Soil compaction tests - Determination of the dry density/water content relationship - Test 4.1.3 New Zealand vibrating hammer compaction test**

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)