Skip to main content Skip to primary navigation Menu Menu
 Home Home About this portal Latest updates
Print Save Email Resource detail Citations
NZS 4402.4.2.2:1988 Methods of testing soils for civil engineering purposes - Soil compaction tests -Determination of the minimum and maximum dry densities and relative density of a cohesionless soil - Test 4.2.2 Maximum dry density
View on Information Provider website {{ linkText }}

Abbreviation NZS 4402.4.2.2:1988 Valid from 31/12/1987 Information provider Standards New Zealand **Author** Standards New Zealand Information type New Zealand Standard Format PDF Cited By This resource is cited by 11 documents (show Citations) Cites This resource cites 1 document (show Citations)

Description

This test method provides a standard technique for the laboratory determination of the maximum dry density of a cohesionless soil and by vibratory compaction of a fully saturated sample. The laboratory density may be used for comparison with feild determinations but should not be considered to be absolute values.

For assistance with locating previous versions, please contact the information provider.

View on Information Provider website {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

NZS 4402.4.2.2:1988 Methods of testing soils for civil engineering purposes - Soil compaction tests -Determination of the minimum and maximum dry densities and relative density of a cohesionless soil - Test 4.2.2 Maximum dry density

This document is CITED BY:

• B1/VM1 (First edition, Amendment 10)

NZS 4402.4.2.2:1988 is cited by Verification Method B1/VM1: Structure - General from 01/07/1992

• B1/VM1 (First edition, amendment 15)

NZS 4402.4.2.2:1988 is cited by Verification Method B1/VM1: Structure - General from 01/07/1992

• B1/VM1 (First Edition, Amendment 12.)

NZS 4402.4.2.2:1988 is cited by Verification Method B1/VM1: Structure - General from 01/07/1992

• B1/VM1 (First edition, Amendment 13)

NZS 4402.4.2.2:1988 is cited by Verification Method B1/VM1: Structure - General from 01/07/1992

• B1/VM1 (First edition, Amendment 16)

NZS 4402.4.2.2:1988 is cited by Verification Method B1/VM1: Structure - General from 01/07/1992

• B1/VM1 (First Edition, Amendment 11)

NZS 4402.4.2.2:1988 is cited by Verification Method B1/VM1: Structure - General from 01/07/1992

• B1/VM1 (First Edition, Amendment 17)

NZS 4402.4.2.2:1988 is cited by Verification Method B1/VM1: Structure - General from 01/07/1992

• B1/VM1 (First edition, Amendment 14)

NZS 4402.4.2.2:1988 is cited by Verification Method B1/VM1: Structure - General from 01/07/1992

AS/NZS 2566.2:2002

NZS 4402.4.2.2:1988 is cited by AS/NZS 2566.2:2002 Buried Flexible pipelines - Installation

AS/NZS 3725:2007

NZS 4402.4.2.2:1988 is cited by AS/NZS 3725:2007 Design for installation of buried concrete pipes

NZS 4402.4.2.3:1988

NZS 4402.4.2.2:1988 is cited by NZS 4402.4.2.3:1988 Methods of testing soils for civic engineering purposes - Soil compaction tests - Determination of the minimum and maximum dry densities and relative density of a cohesionless soil - Test 4.2.3 Relative density

Back

NZS 4402.4.2.2:1988 Methods of testing soils for civil engineering purposes - Soil compaction tests -Determination of the minimum and maximum dry densities and relative density of a cohesionless soil - Test 4.2.2 Maximum dry density

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This test method provides a standard technique for the laboratory determination of the maximum dry density of a cohesionless soil and by vibratory compaction of a fully saturated sample. The laboratory density may be used for comparison with feild determinations but should not be considered to be absolute values.

View on Information Provider website

NZS 4402.4.2.2:1988 Methods of testing soils for civil engineering purposes - Soil compaction tests - Determination of the minimum and maximum dry densities and relative density of a cohesionless soil - Test 4.2.2 Maximum dry density

Description

This test method provides a standard technique for the laboratory determination of the maximum dry density of a cohesionless soil and by vibratory compaction of a fully saturated sample. The laboratory density may be used for comparison with feild determinations but should not be considered to be absolute values.

View on Information Provider website

This resource cites:

NZS 4402.4.2.2:1988 Methods of testing soils for civil engineering purposes - Soil compaction tests -Determination of the minimum and maximum dry densities and relative density of a cohesionless soil - Test 4.2.2 Maximum dry density

This document CITES:

New Zealand Standards

NZS 4402.1:1986

NZS 4402.4.2.2:1988 cites NZS 4402.1:1986 Methods of testing soils for civil engineering purposes - Part 1: Preliminary and general



Table of Contents

Print Sav	<u>re</u> Email					
Feedback						
			_			

Contact us

- Privacy policy Disclaimer
- Copyright

<u>Feedback</u>