

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

## **NZS 4402.6.2.1:1986 Methods of testing soils for civil engineering purposes - Soil strength tests - Determination of the compressive strength of specimens tested in undrained triaxial compression - Test 6.2.1 Method without measurement of pore water press**

[View on Information Provider website](#)

Abbreviation

NZS 4402.6.2.1:1986

Valid from

31/12/1985

---

Information provider

Standards New Zealand

Author

Standards New Zealand

Information type

New Zealand Standard

Format

PDF

---

**Description**

Covers the determination of the compressive strength of specimens of soil in the triaxial compression apparatus under conditions in which the cell pressure is maintained constant, and there is no change in the water content of the specimens.

The test is limited to specimens in the form of right cylinders of height approximately equal to twice the diameter. To be read in conjunction with Part 1.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

## **NZS 4402.6.2.1:1986 Methods of testing soils for civil engineering purposes - Soil strength tests - Determination of the compressive strength of specimens tested in undrained triaxial compression - Test 6.2.1 Method without measurement of pore water press**

This document is not CITED BY any other resources:

## **NZS 4402.6.2.1:1986 Methods of testing soils for civil engineering purposes - Soil strength tests - Determination of the compressive strength of specimens tested in undrained triaxial compression - Test 6.2.1 Method without measurement of pore water press**

### **Description**

Covers the determination of the compressive strength of specimens of soil in the triaxial compression apparatus under conditions in which the cell pressure is maintained constant, and there is no change in the water content of the specimens.

The test is limited to specimens in the form of right cylinders of height approximately equal to twice the diameter. To be read in conjunction with Part 1.

[View on Information Provider website](#)

[NZS 4402.6.2.1:1986 Methods of testing soils for civil engineering purposes - Soil strength tests - Determination of the compressive strength of specimens tested in undrained triaxial compression - Test 6.2.1 Method without measurement of pore water press](#)

## Description

Covers the determination of the compressive strength of specimens of soil in the triaxial compression apparatus under conditions in which the cell pressure is maintained constant, and there is no change in the water content of the specimens.

The test is limited to specimens in the form of right cylinders of height approximately equal to twice the diameter. To be read in conjunction with Part 1.

[View on Information Provider website](#)

This resource does not cite any other resources.

# **NZS 4402.6.2.1:1986 Methods of testing soils for civil engineering purposes - Soil strength tests - Determination of the compressive strength of specimens tested in undrained triaxial compression - Test 6.2.1 Method without measurement of pore water press**

This resource does not CITE any other resources.

Back

Close

## Table of Contents

Print

[Save](#)

Email

[Feedback](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
----------------------	----------------------	----------------------

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
----------------------	----------------------	----------------------

[Feedback](#)