

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  

[Save](#)

[Resource detail](#)  
[Citations](#)

## AS/NZS 4793:2009 Mechanical tapping bands for waterworks purposes

[View on Information Provider website](#)

Abbreviation  
AS/NZS 4793:2009  
Valid from  
30/03/2009

---

Information provider  
Standards New Zealand  
Author  
Standards New Zealand, Standards Australia  
Information type  
New Zealand Standard  
Format  
PDF

---

Cited By  
[This resource is cited by 1 document \(show Citations\)](#)

---

### Description

This Standard specifies requirements for design, materials, and performance in service of PN 16 mechanical tapping bands used for the connection of property service pipes to reticulation watermains. It applies to tapping bands, with and without electrical insulation, for mechanical connection to standard watermains, with the exception of tapping bands for polyethylene watermains that are covered in AS/NZS 4129.

The nominal operating temperature range is 0°C to 40°C. Solvent cemented PVC tapping bands are outside the scope of this Standard. The nominal size range of tapping bands covered by this Standard is DN 80 to DN 450 with outlet sizes ranging from DN 15 to DN 50, as appropriate to the tapping band size.

Methods of demonstrating compliance with this Standard are given in Appendix A.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

# AS/NZS 4793:2009 Mechanical tapping bands for waterworks purposes

This document is CITED BY:

- [AS/NZS 3690:2009](#)

AS/NZS 4793:2009 is cited by AS/NZS 3690:2009 Installation of ABS pipe systems

Back

# AS/NZS 4793:2009 Mechanical tapping bands for waterworks purposes

Show what documents this resource is CITED BY

Show what documents this resource CITES

## Description

This Standard specifies requirements for design, materials, and performance in service of PN 16 mechanical tapping bands used for the connection of property service pipes to reticulation watermains. It applies to tapping bands, with and without electrical insulation, for mechanical connection to standard watermains, with the exception of tapping bands for polyethylene watermains that are covered in AS/NZS 4129.

The nominal operating temperature range is 0°C to 40°C. Solvent cemented PVC tapping bands are outside the scope of this Standard. The nominal size range of tapping bands covered by this Standard is DN 80 to DN 450 with outlet sizes ranging from DN 15 to DN 50, as appropriate to the tapping band size.

Methods of demonstrating compliance with this Standard are given in Appendix A.

[View on Information Provider website](#)

[AS/NZS 4793:2009 Mechanical tapping bands for waterworks purposes](#)

## Description

This Standard specifies requirements for design, materials, and performance in service of PN 16 mechanical tapping bands used for the connection of property service pipes to reticulation watermains. It applies to tapping bands, with and without electrical insulation, for mechanical connection to standard watermains, with the exception of tapping bands for polyethylene watermains that are covered in AS/NZS 4129.

The nominal operating temperature range is 0°C to 40°C. Solvent cemented PVC tapping bands are outside the scope of this Standard. The nominal size range of tapping bands covered by this Standard is DN 80 to DN 450 with outlet sizes ranging from DN 15 to DN 50, as appropriate to the tapping band size.

Methods of demonstrating compliance with this Standard are given in Appendix A.

[View on Information Provider website](#)

This resource does not cite any other resources.

# AS/NZS 4793:2009 Mechanical tapping bands for waterworks purposes

This resource does not CITE any other resources.

Back

Close

Table of Contents

## Section 1 Scope And General

## **1.1 Scope**

## **1.2 Referenced Documents**

## **1.3 Definitions**

## **1.4 Designation Of Size**

## **1.5 Allowable Pressures**

## **Section 2 Materials**

### **2.1 Material Requirements**

### **2.2 Dezincification-Resistant Materials**

### **2.3 Stainless Steel**

### **2.4 Plastics Materials**

### **2.5 Coating**

### **2.6 Elastomeric Seals**

### **2.7 Effect On Water**

## **Section 3 Design**

### **3.1 Tapping Band Components**

### **3.2 Fitment**

### **3.3 Tapping Band Types**

### **3.4 Means Of Attachment**

### **3.5 Fasteners**

### **3.6 Outlets**

### **3.7 Bi-Metallic Contact**

### **3.8 Freedom From Defects**

## **Section 4 Testing**

### **4.1 Type Tests**

### **4.2 Bi-Metallic Couple**

## 4.3 Integrated Assembly

### Section 5 Marking And Packaging

#### 5.1 Marking

#### 5.2 Packaging

#### 5.3 Installation Instructions And Pipe Compatibility

### Appendices

#### Appendix A - Compliance Requirements

#### Appendix B - Assembly Test

#### Appendix C - Leak tightness Test During Application Of A Bending Moment To The Connecting Pipe

#### Appendix D - Resistance To Depressurization And Rotational And Sliding Movement

[Save](#)

[Feedback](#)

  
    

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

    

[Feedback](#)