

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

AS/NZS 4999:2006 PVC-U maintenance shafts

[View on Information Provider website](#)

Abbreviation

AS/NZS 4999:2006

Valid from

27/03/2006

Information provider

Standards New Zealand

Author

Standards New Zealand, Standards Australia

Information type

New Zealand Standard

Format

PDF

Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

Description

This Standard specifies design and manufacture requirements for a PVC-U maintenance shaft (MS) comprising a fabricated or injection-moulded, or both, chamber jointed to an extruded PVC riser.

Scope

MSs are intended for installation in sewerage systems (up to DN 300) for transportation of sewage at atmospheric pressure and average service temperatures up to 25°C. They are intended for buried vertical installation at depths up to 6 m, without buckling or collapse and without exceeding specified long-term diametral distortion and stress limits.

Long-term design criteria limits are 50-year extrapolated or predicted values. Provided installation and operating conditions conform to the guidelines in this Standard, life expectancy may exceed 50 years.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS/NZS 4999:2006 PVC-U maintenance shafts

This document is CITED BY:

- [AS/NZS 3500.2:2015](#)

AS/NZS 4999:2006 is cited by AS/NZS 3500.2:2015 Plumbing and drainage - Part 2: Sanitary plumbing and drainage

- [AS/NZS 3500.2:2018](#)

AS/NZS 4999:2006 is cited by AS/NZS 3500.2:2018 Plumbing and drainage Part 2: Sanitary plumbing and drainage

Back

AS/NZS 4999:2006 PVC-U maintenance shafts

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard specifies design and manufacture requirements for a PVC-U maintenance shaft (MS) comprising a fabricated or injection-moulded, or both, chamber jointed to an extruded PVC riser.

[View on Information Provider website](#)

[AS/NZS 4999:2006 PVC-U maintenance shafts](#)

Description

This Standard specifies design and manufacture requirements for a PVC-U maintenance shaft (MS) comprising a fabricated or injection-moulded, or both, chamber jointed to an extruded PVC riser.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS/NZS 4999:2006 PVC-U maintenance shafts

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)