

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  

[Save](#)

[Resource detail](#)  
[Citations](#)

## AS TR 5058:2009 Temperature rerating of PVC pressure pipes operating at elevated temperatures

[View on Information Provider website](#)

### Abbreviation

AS TR 5058:2009

### Valid from

08/05/2009

---

### Information provider

SAI Global

### Author

Standards Australia

### Information type

Technical report

### Format

PDF

---

### Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

### Description

This Technical Report presents a method for rerating PVC pressure pipes operating at temperatures above 20°C and below 50°C. It applies to pressure pipes made of unplasticized PVC (PVC-U), modified PVC (PVC-M) and oriented PVC (PVC-O).

### Scope

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## AS TR 5058:2009 Temperature rerating of PVC pressure pipes operating at elevated temperatures

This document is CITED BY:

- [NZS 4515:2009](#)

AS TR 5058:2009 is cited by NZS 4515:2009 Fire sprinkler systems for life safety in sleeping occupancies (up to 2000 square metres)

Back

## AS TR 5058:2009 Temperature rerating of PVC pressure pipes operating at elevated temperatures

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

This Technical Report presents a method for rerating PVC pressure pipes operating at temperatures above 20°C and below 50°C. It applies to pressure pipes made of unplasticized PVC (PVC-U), modified PVC (PVC-M) and oriented PVC (PVC-O).

[View on Information Provider website](#)

[AS TR 5058:2009 Temperature rerating of PVC pressure pipes operating at elevated temperatures](#)

### Description

This Technical Report presents a method for rerating PVC pressure pipes operating at temperatures above 20°C and below 50°C. It applies to pressure pipes made of unplasticized PVC (PVC-U), modified PVC (PVC-M) and oriented PVC (PVC-O).

[View on Information Provider website](#)

This resource does not cite any other resources.

## AS TR 5058:2009 Temperature rerating of PVC pressure pipes operating at elevated temperatures

This resource does not CITE any other resources.

Back

Close

### Table of Contents

Print [Save](#) Email

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)