Skip to main content Skip Men			
 Home Home About this portal Latest updates			
Print Save Email	-	-	

NZS 7602:1977 Specification for polyethylene pipe (Type 5) for cold water services

Table of Contents

<u>View on Information Provider website Download this resource (PDF, 2.9MB)</u> {{ linkText }}

Abbreviation

Citations

NZS 7602:1977

Amendment

Amendment 1 - appended. Published 29/09/1978.

Valid from

30/11/1977

Information provider

Standards New Zealand

Author

Standards New Zealand

Information type

New Zealand Standard

Format

PDF

Cited By

This resource is cited by 7 documents (show Citations)

Cites

This resource cites 3 documents (show Citations)

Description

This Standard sets out the material, dimensions, properties, tests and marking requirements for black polyethylene pipe of Type 5 for use in cold water services, and in flush, overflow, warning and waste-pipe applications. The type designation refers to the maximum working stress of the material at 20 degrees C, in megapascals, when in pipe form.

For assistance with locating previous versions, please contact the information provider.

Table of Contents View on Information Provider website Download this resource (PDF, 2.9MB) {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

NZS 7602:1977 Specification for polyethylene pipe (Type 5) for cold water

services

This document is CITED BY:

• G12/AS1 (Third Edition, Amendment 10)

NZS 7602:1977 is cited by Acceptable Solution G12/AS1: Water Supplies from 01/12/2007

• G12/AS1 (Third Edition, Amendment 8)

NZS 7602:1977 is cited by Acceptable Solution G12/AS1: Water Supplies from 01/12/2007

• G12/AS1 (Third Edition, Amendment 12)

NZS 7602:1977 is cited by Acceptable Solution G12/AS1: Water Supplies from 01/12/2007

• G12/AS1 (Third Edition, Amendment 7)

NZS 7602:1977 is cited by Acceptable Solution G12/AS1: Water Supplies from 01/12/2007

• G12/AS1 (Third Edition, Amendment 9)

NZS 7602:1977 is cited by Acceptable Solution G12/AS1: Water Supplies from 01/12/2007

• G12/AS1 (Third Edition, Amendment 11)

NZS 7602:1977 is cited by Acceptable Solution G12/AS1: Water Supplies from 01/12/2007

NZS 4614:1986

NZS 7602:1977 is cited by NZS 4614:1986 Installation of domestic solar water heating systems

Back

NZS 7602:1977 Specification for polyethylene pipe (Type 5) for cold water services

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard sets out the material, dimensions, properties, tests and marking requirements for black polyethylene pipe of Type 5 for use in cold water services, and in flush, overflow, warning and waste-pipe applications. The type designation refers to the maximum working stress of the material at 20 degrees C, in megapascals, when in pipe form.

View on Information Provider website Download this resource (PDF, 2.9MB)

NZS 7602:1977 Specification for polyethylene pipe (Type 5) for cold water services

Description

This Standard sets out the material, dimensions, properties, tests and marking requirements for black polyethylene pipe of Type 5 for use in cold water services, and in flush, overflow, warning and waste-pipe applications. The type designation refers to the maximum working stress of the material at 20 degrees C, in megapascals, when in pipe form.

View on Information Provider website Download this resource (PDF, 2.9MB)

This resource cites:

NZS 7602:1977 Specification for polyethylene pipe (Type 5) for cold water services

Other

• BS 1792:1960

NZS 7602:1977 cites BS 1792:1960 One-mark volumetric flasks

• BS 2782

NZS 7602:1977 cites BS 2782 Introduction:1975 Methods of testing plastics

• BS 572:1960

NZS 7602:1977 cites BS 572:1960 Interchangeable conical ground glass joints



Table of Contents

- 1 Scope
- 2 Interpretation
- 3 Classification
- **4 Composition**
- 5 Freedom from defects
- 6 Dimensions
- 7 Packing
- 8 Hydrostatic test
- 9 Heat reversion test
- 10 Tensile test (type test)
- 11 Marking

Figure

- 1-6 Satisfactory dispersion of pigment
- 7-12 Unsatisfactory dispersion of pigment
- 13 Suitable end connections for hydrostatic test

Table

1 Pipe dimensions

2 Distance between supports

Appendix

A Method for the determination of toluene extract of carbon black

B Method for the determination of 1,1-di-(3-terbutyl-4-hydroxy-6-methylphenyl) butane

C Hydrostatic test

D Heat resistance test

E Tensile test\

F Notes on the use of polyethylene pipe (type 5) for cold water services

Print Save Email			
Feedback			
	_	_	
Contact usPrivacy policyDisclaimerCopyright			
<u>Feedback</u>			