

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)

[Citations](#)

# API STD 5B Specification for Threading, Gaging, and Thread Inspection of Casing, Tubing, and Line Pipe Threads

[View on Information Provider website](#)

{{ linkText }}

Abbreviation

API STD 5B

Valid from

31/05/1988

---

Information provider

GlobalSpec

Author

American Petroleum Institute

Information type

Other Standard

Format

PDF

---

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

## Description

This specification covers dimensional requirements on threads and thread gages and stipulations on gaging practice, gage specifications and certification as well as the instruments and methods for the inspection of threads for line pipe, round-thread casing and tubing, buttress casing and extreme-line casing joints. It is applicable when so stipulated in the API standard governing the product. The inspection procedures for measurements of taper, lead, height, and angle of thread are applicable only to threads having 1 1½ or less turns per inch. All thread dimensions shown without tolerances

are related to the basis for joint design and are not subject to measurement to determine acceptance or rejection of product.

Thread inspection applies at the point of manufacture prior to shipment, to inspection at any intermediate point, to inspection subsequent to delivery at destination, and to inspection by inspectors representing the purchaser or the manufacturer. The manufacturer may, at his option, use other instruments or methods to control manufacturing operations; but acceptance and rejection of the product shall be governed solely by the results of inspection made in accordance with the requirements of this specification.

Although this specification contains complete dimensional information for threading and gaging buttress and extreme-line casing joints, considerable skill and know-how is required for the tooling for, and machining of, these joints. Therefore, any manufacturer who desires to produce these joints is advised to consult with manufacturers who have produced these joints before attempting their manufacture.

This specification is under the jurisdiction of the API Committee on Standardization of Tubular Goods.

- 1. *Shall* is used to indicate that a provision is mandatory.
- 2. *Should* is used to indicate that a provision is not mandatory, but recommended as good practice.
- 3. *May* is used to indicate that a provision is optional.

The applicable product specification should be consulted for requirements on pipe and couplings not given herein.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

# API STD 5B Specification for Threading, Gaging, and Thread Inspection of Casing, Tubing, and Line Pipe Threads

This document is CITED BY:

- [API SPEC 5L-1991](#)

API STD 5B is cited by API SPEC 5L-1991 Specification for line pipe

Back

# API STD 5B Specification for Threading, Gaging, and Thread Inspection of Casing, Tubing, and Line Pipe Threads

Show what documents this resource is CITED BY

Show what documents this resource CITES

## Description

This specification covers dimensional requirements on threads and thread gages and stipulations on gaging practice, gage specifications and certification as well as the instruments and methods for the inspection of threads for line pipe, round-thread casing and tubing, buttress casing and extreme-line casing joints. It is applicable when so stipulated in the API standard governing the product. The inspection procedures for measurements of taper, lead, height, and angle of thread are applicable only to threads having 1 1/2 or less turns per inch. All thread dimensions shown without tolerances are related to the basis for joint design and are not subject to measurement to determine acceptance or rejection of product.

Thread inspection applies at the point of manufacture prior to shipment, to inspection at any intermediate point, to inspection subsequent to delivery at destination, and to inspection by inspectors representing the purchaser or the manufacturer. The manufacturer may, at his option, use other instruments or methods to control manufacturing operations; but acceptance and rejection of the product shall be governed solely by the results of inspection made in accordance with the requirements of this specification.

Although this specification contains complete dimensional information for threading and gaging buttress and extreme-line casing joints, considerable skill and know-how is required for the tooling for, and machining of, these joints. Therefore, any manufacturer who desires to produce these joints is advised to consult with manufacturers who have produced these joints before attempting their manufacture.

This specification is under the jurisdiction of the API Committee on Standardization of Tubular Goods.

1. *Shall* is used to indicate that a provision is mandatory.
2. *Should* is used to indicate that a provision is not mandatory, but recommended as good practice.
3. *May* is used to indicate that a provision is optional.

The applicable product specification should be consulted for requirements on pipe and couplings not given herein.

[View on Information Provider website](#)

[API STD 5B Specification for Threading, Gaging, and Thread Inspection of Casing, Tubing, and Line Pipe Threads](#)

## Description

This specification covers dimensional requirements on threads and thread gages and stipulations on gaging practice, gage specifications and certification as well as the instruments and methods for the inspection of threads for line pipe, round-thread casing and tubing, buttress casing and extreme-line casing joints. It is applicable when so stipulated in the API standard governing the product. The inspection procedures for measurements of taper, lead, height, and angle of thread are applicable only to threads having 1 1½ or less turns per inch. All thread dimensions shown without tolerances are related to the basis for joint design and are not subject to measurement to determine acceptance or rejection of product.

Thread inspection applies at the point of manufacture prior to shipment, to inspection at any intermediate point, to inspection subsequent to delivery at destination, and to inspection by inspectors representing the purchaser or the manufacturer. The manufacturer may, at his option, use other instruments or methods to control manufacturing operations; but acceptance and rejection of the product shall be governed solely by the results of inspection made in accordance with the requirements of this specification.

Although this specification contains complete dimensional information for threading and gaging buttress and extreme-line casing joints, considerable skill and know-how is required for the tooling for, and machining of, these joints. Therefore, any manufacturer who desires to produce these joints is advised to consult with manufacturers who have produced these joints before attempting their manufacture.

This specification is under the jurisdiction of the API Committee on Standardization of Tubular Goods.

1. *Shall* is used to indicate that a provision is mandatory.
2. *Should* is used to indicate that a provision is not mandatory, but recommended as good practice.
3. *May* is used to indicate that a provision is optional.

The applicable product specification should be consulted for requirements on pipe and couplings not given herein.

[View on Information Provider website](#)

This resource does not cite any other resources.

## API STD 5B Specification for Threading, Gaging, and Thread Inspection of Casing, Tubing, and Line Pipe Threads

This resource does not CITE any other resources.

Back

Close

Table of Contents

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)