

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  

[Save](#)

[Resource detail](#)  
[Citations](#)

## Triclad EnduroClad Board and Batten cladding system

[Download this resource \(PDF, 556KB\)](#)

### Abbreviation

Appraisal number 1063

### Valid from

13/12/2019

---

### Information provider

BRANZ Limited

### Information type

BRANZ Appraisal

### Format

PDF

---

### Description

The Triclad EnduroClad™ Board and Batten cladding system is a cavity based or direct fixed plywood sheet wall cladding. It is designed to be used as an external cladding system for residential and light commercial type buildings where domestic construction techniques are used.

The Triclad EnduroClad™ Board and Batten cladding system consists of Triclad EnduroClad™ Boards plywood sheets with a bandsawn textured exterior surface overlaid with vertical timber battens at the joints and spaced throughout to simulate the look of traditional board and batten weatherboards. Triclad EnduroClad™ Boards can be installed as a direct fixed cladding system, or over cavity battens to form a drained and vented cavity. Triclad EnduroClad™ is available either unprimed or pre primed suitable for finishing with an exterior grade acrylic paint. Triclad EnduroClad™ can also be supplied with first finishing coat of the selected finishing system applied.

### Scope

The Triclad EnduroClad™ Board and Batten cladding system has been appraised for as a direct fixed external wall cladding for buildings within the following scope:

- the scope limitations of NZBC Acceptable Solution E2/AS1 Paragraph 1.1; and,
- with a risk score of 0-6, calculated in accordance with NZBC Acceptable Solution E2/AS1, Table 2; and,
- situated in NZS 3604 Wind Zones up to and including Extra High.

The Triclad EnduroClad™ Board and Batten cladding system has also been appraised as a cavity-based external wall cladding for buildings within the following scope:

- the scope limitations of NZBC Acceptable Solution E2/AS1 Paragraph 1.1; and,
- with a risk score of 0-20, calculated in accordance with NZBC Acceptable Solution E2/AS1, Table 2; and,
- situated in NZS 3604 Wind Zones up to and including Extra High.

The Triclad EnduroClad™ Board and Batten cladding system must only be installed vertically on vertical surfaces.

The Triclad EnduroClad™ Board and Batten cladding system is appraised for use with aluminium window and door joinery that is installed with vertical jambs and horizontal heads and sills. (Note: The Triclad EnduroClad™ Board and Batten cladding system relies on the joinery meeting the requirements of NZS 4211 for the relevant Wind Zone.)

For assistance with locating previous versions, please contact the information provider.

[Download this resource \(PDF, 556KB\)](#)

For assistance with locating previous versions, please contact the information provider.

This resource is not cited by any other resources.

## Triclad EnduroClad Board and Batten cladding system

This document is not CITED BY any other resources:

## Triclad EnduroClad Board and Batten cladding system

### Description

The Triclad EnduroClad™ Board and Batten cladding system is a cavity based or direct fixed plywood sheet wall cladding. It is designed to be used as an external cladding system for residential and light commercial type buildings where domestic construction techniques are used.

The Triclad EnduroClad™ Board and Batten cladding system consists of Triclad EnduroClad™ Boards plywood sheets with a bandsawn textured exterior surface overlaid with vertical timber battens at the joints and spaced throughout to simulate the look of traditional board and batten weatherboards. Triclad EnduroClad™ Boards can be installed as a direct fixed cladding system, or over cavity battens to form a drained and vented cavity. Triclad EnduroClad™ is available either unprimed or pre primed suitable for finishing with an exterior grade acrylic paint. Triclad EnduroClad™ can also be supplied with first finishing coat of the selected finishing system applied.

[Download this resource \(PDF, 556KB\)](#)

[Triclad EnduroClad Board and Batten cladding system](#)

### Description

The Triclad EnduroClad™ Board and Batten cladding system is a cavity based or direct fixed plywood sheet wall cladding. It is designed to be used as an external cladding system for residential and light commercial type buildings where domestic construction techniques are used.

The Triclad EnduroClad™ Board and Batten cladding system consists of Triclad EnduroClad™ Boards plywood sheets with a bandsawn textured exterior surface overlaid with vertical timber battens at the joints and spaced throughout to simulate the look of traditional board and batten weatherboards. Triclad EnduroClad™ Boards can be installed as a direct fixed cladding system, or over cavity battens to form a drained and vented cavity. Triclad EnduroClad™ is available either unprimed or pre primed suitable for finishing with an exterior grade acrylic paint. Triclad EnduroClad™ can also be supplied with first finishing coat of the selected finishing system applied.

[Download this resource \(PDF, 556KB\)](#)

This resource does not cite any other resources.

# Triclad EnduroClad Board and Batten cladding system

This resource does not CITE any other resources.

Back

Close

## Table of Contents

Print

[Save](#)

Email

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)