

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  

[Save](#)

[Resource detail](#)  
[Citations](#)

## Gorilla MS Sealant

[View on Information Provider website](#) [Download this resource \(PDF, 442KB\)](#)

Abbreviation  
Appraisal number 419  
Amendment  
20 March 2020  
Valid from  
28/07/2017

---

Information provider  
BRANZ Limited  
Information type  
BRANZ Appraisal  
Format  
PDF

---

### Description

Gorilla MS Sealant is a waterproof, elastic, UV resistant joint sealant for interior and exterior applications.

### Scope

Gorilla MS Sealant has been appraised for use as an exterior sealant in buildings within the following scope:

- the scope limitations of NZBC Acceptable Solution E2/AS1, Paragraph 1.1.

Gorilla MS Sealant has also been appraised for use as an internal and external sealant in buildings subject to specific design within the following scope:

- in joints with a minimum width of 5 mm and maximum width of 30 mm, or 40 mm when a threepass method of installation is used; and,
- with substrates of:
  - timber (unpainted and unstained) – particleboard, fibreboard, untreated pine, boron treated pine, tanalised pine, New Zealand natives or untreated Cedar or Douglas Fir; or,
  - plastics – PVC, melamine sheet, fibreglass (gelcoat side only), polyurethane coatings, epoxy and polyester coatings or epoxy mortars; or,
  - metals – stainless steel, aluminium-zinc, lead, tin, galvanised steel, mild steel, cast iron or aluminium (milled, anodised or powder coated); or,
  - mineral - concrete, mortar, plaster, blockwork, brickwork, fibre cement sheeting, unglazed tiles, earthenware (clay), glazed ceramic tiles, stoneware (e.g. Hinuera stone and Oamaru stone), marble or granite; or,
  - glass fibre reinforced concrete; or,
  - glass and ceramics; or,
  - butyl rubber products.

*Note: Substrates or materials other than those specified above have not been assessed and are outside the scope of this Appraisal. Holdfast NZ Ltd must be consulted when proposing the sealing of material not specifically covered by this Appraisal.*

For assistance with locating previous versions, please contact the information provider.

Notes/comments

This Appraisal replaces BRANZ Appraisal No. 419 (2011).

[View on Information Provider website](#) [Download this resource \(PDF, 442KB\)](#)

For assistance with locating previous versions, please contact the information provider.

This Appraisal replaces BRANZ Appraisal No. 419 (2011).

This resource is not cited by any other resources.

## Gorilla MS Sealant

This document is not CITED BY any other resources:

## Gorilla MS Sealant

Description

Gorilla MS Sealant is a waterproof, elastic, UV resistant joint sealant for interior and exterior applications.

[View on Information Provider website](#) [Download this resource \(PDF, 442KB\)](#)

[Gorilla MS Sealant](#)

Description

Gorilla MS Sealant is a waterproof, elastic, UV resistant joint sealant for interior and exterior applications.

[View on Information Provider website](#) [Download this resource \(PDF, 442KB\)](#)

This resource does not cite any other resources.

## Gorilla MS Sealant

This resource does not CITE any other resources.

Table of Contents

 [Save](#) 

[Feedback](#)

|  |
|--|
|  |
|  |
|  |

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

|  |  |  |
|--|--|--|
|  |  |  |
|--|--|--|

[Feedback](#)