| Skip to main content Skip to pr | <u>imary navigation</u> | |
|--|-------------------------|--|
| Menu | | |
| Home HomeAbout this portalLatest updates | | |
| | | |
| Print Save Email | | |
| Resource detail | | |

Nuraply Roof and Deck Membranes

View on Information Provider website Download this resource (PDF, 963KB) {{ linkText }}

Abbreviation
Appraisal number 547
Valid from
15/10/2019

Information provider
BRANZ Limited
Information type
BRANZ Appraisal
Format
PDF

Description

Citations

Nuraply Roof and Deck Membranes are waterproofing membranes for nominally flat and pitched roofs and decks. They are installed as a multi-layer system with either a mineral chip finished product or a UV protective paint as the top layer or as a single layer system onto a concrete substrate under heavy protection such as paving slabs or a topping screed.

Scope

Nuraply Roof and Deck Membranes have been appraised as roof and deck waterproofing membranes on buildings within the following scope:

- the scope limitations of NZBC Acceptable Solution E2/AS1, Paragraph 1.1; or,
- the scope of limitations of NZBC Acceptable Solution E2/AS1, Paragraph 1.1 with regards to building height and floor plan area when subject to specific structural design; and,
- with substrates of plywood or suspended concrete slab; and,
- with minimum falls for roofs of 1:30, plywood decks of 1:40; and suspended concrete slab of 1:60; and
- with deck size limited to 40 m2; and,
- situated in NZS 3604 Wind Zones, up to, and including Extra High.

Nuraply Roof and Deck Membranes have also been appraised as roof and deck waterproofing membranes on buildings within the following scope:

- subject to specific structural and weathertightness design; and,
- with substrates of plywood or suspended concrete slab; and,
- situated in specific design wind pressures up to a maximum design differential ultimate limit state (ULS) of 6 kPa; and,
- with the weathertightness design of junctions for each specific structure being the responsibility of the building designer.

Roofs and decks waterproofed with Nuraply Roof and Deck Membranes must be designed and constructed in accordance with the following limitations:

 nominally flat or pitched roofs and decks constructed to drain water to gutters and drainage outlets complying with the NZBC; and,

- with no steps within the deck level, no integral roof gardens and no downpipe direct discharge to the deck; and.
- with the deck membranes continually protected from physical damage by a pedestal protection system.

The design and construction of the substrate and movement and control joints is specific to each building, and therefore is the responsibility of the building designer and building contractor and **is outside the scope** of this Appraisal.

The membranes must be installed by Nuralite Waterproofing Ltd. Trained and Approved Installers.

For assistance with locating previous versions, please contact the information provider.

Notes/comments

This Appraisal replaces BRANZ Appraisal number 547 (2014).

<u>View on Information Provider website Download this resource (PDF, 963KB)</u> {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This Appraisal replaces BRANZ Appraisal number 547 (2014).

This resource is not cited by any other resources.

Nuraply Roof and Deck Membranes

This document is not CITED BY any other resources:

Back

Nuraply Roof and Deck Membranes

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

Nuraply Roof and Deck Membranes are waterproofing membranes for nominally flat and pitched roofs and decks. They are installed as a multi-layer system with either a mineral chip finished product or a UV protective paint as the top layer or as a single layer system onto a concrete substrate under heavy protection such as paving slabs or a topping screed.

View on Information Provider website Download this resource (PDF, 963KB)

Nuraply Roof and Deck Membranes

Description

Nuraply Roof and Deck Membranes are waterproofing membranes for nominally flat and pitched roofs and decks. They are installed as a multi-layer system with either a mineral chip finished product or a UV protective paint as the top layer or as a single layer system onto a concrete substrate under heavy protection such as paving slabs or a topping screed.

View on Information Provider website Download this resource (PDF, 963KB)

This resource does not cite any other resources.

Nuraply Roof and Deck Membranes

This resource does not CITE any other resources.

Back

| Close |
|-------|
| 0.000 |

Table of Contents

| Print Save Email | |
|---|---|
| <u>Feedback</u> | |
| | |
| | |
| | |
| Combant | |
| <u>Contact us</u><u>Privacy policy</u> | |
| • <u>Disclaimer</u> | |
| • Copyright | |
| | |
| | |
| | _ |

Feedback