

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

Save

Email

[Resource detail](#)
[Citations](#)

J-Frame LVL Framing

[View on Information Provider website](#) [Download this resource \(PDF, 708KB\)](#)

{{ linkText }}

Abbreviation
Appraisal number 646
Amendment
28/09/2020
Valid from
13/09/2019

Information provider
BRANZ Limited
Information type
BRANZ Appraisal
Format
PDF

Description

J-Frame LVL Framing is laminated veneer lumber (LVL) structural framing timber available as 90 x 45 mm, 140 x 45 mm, 190 x 45 mm, 240 x 45 mm and 300 x 45 mm sections. It is boron preservative treated.

Scope

J-Frame LVL Framing has been appraised for use as structural framing timber for non-specifically designed timber-framed buildings designed and constructed in accordance with NZS 3604 and specifically designed buildings in accordance with NZS 3603.

J-Frame LVL Framing has been appraised as an alternative to radiata pine solid timber, treated such that it is suitable for use where hazard class H1.2 applies.

For assistance with locating previous versions, please contact the information provider.

Notes/comments

This Appraisal replaces BRANZ Appraisal No. 646 (2014).

[View on Information Provider website](#) [Download this resource \(PDF, 708KB\)](#)

{{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This Appraisal replaces BRANZ Appraisal No. 646 (2014).

This resource is not cited by any other resources.

J-Frame LVL Framing

Back

J-Frame LVL Framing

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

J-Frame LVL Framing is laminated veneer lumber (LVL) structural framing timber available as 90 x 45 mm, 140 x 45 mm, 190 x 45 mm, 240 x 45 mm and 300 x 45 mm sections. It is boron preservative treated.

[View on Information Provider website](#) [Download this resource \(PDF, 708KB\)](#)

J-Frame LVL Framing

Description

J-Frame LVL Framing is laminated veneer lumber (LVL) structural framing timber available as 90 x 45 mm, 140 x 45 mm, 190 x 45 mm, 240 x 45 mm and 300 x 45 mm sections. It is boron preservative treated.

[View on Information Provider website](#) [Download this resource \(PDF, 708KB\)](#)

This resource does not cite any other resources.

J-Frame LVL Framing

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print

[Save](#)

Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)