

- [Home](#) [Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)
[Citations](#)

AS 1159-1988 Polyethylene pipes for pressure applications

[View on Information Provider website](#)

{{ linkText }}

Abbreviation
AS 1159-1988
Valid from
05/04/1988

Information provider
SAI Global
Author
Standards Australia
Information type
Australian Standard
Format
PDF

Cited By
[This resource is cited by 1 document \(show Citations\)](#)

Description

This Standard specifies polyethylene pipe for water supply, agriculture, industrial, and other applications, excluding gaseous fuel reticulation. It nominates two types of extrusion compound in AS 1463, for six classes according to maximum working pressure. Nominal outside diameter range of 12-1600 mm. Appendices contain tests for pipe dimensions, resistance to internal pressure and pipe reversion characteristics.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

{{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 1159-1988 Polyethylene pipes for pressure applications

This document is CITED BY:

- [NZS 4332:1997](#)
AS 1159-1988 is cited by NZS 4332:1997 Non-domestic passenger and goods lifts

Back

AS 1159-1988 Polyethylene pipes for pressure applications

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard specifies polyethylene pipe for water supply, agriculture, industrial, and other applications, excluding gaseous fuel reticulation. It nominates two types of extrusion compound in AS 1463, for six classes according to maximum working pressure. Nominal outside diameter range of 12-1600 mm. Appendices contain tests for pipe dimensions, resistance to internal pressure and pipe reversion characteristics.

[View on Information Provider website](#)

[AS 1159-1988 Polyethylene pipes for pressure applications](#)

Description

This Standard specifies polyethylene pipe for water supply, agriculture, industrial, and other applications, excluding gaseous fuel reticulation. It nominates two types of extrusion compound in AS 1463, for six classes according to maximum working pressure. Nominal outside diameter range of 12-1600 mm. Appendices contain tests for pipe dimensions, resistance to internal pressure and pipe reversion characteristics.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS 1159-1988 Polyethylene pipes for pressure applications

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print

[Save](#)

Email

[Feedback](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
----------------------	----------------------	----------------------

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
----------------------	----------------------	----------------------

[Feedback](#)