

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Resource detail](#)
[Citations](#)

AS 1289.5.4.1-1993 Methods of testing soils for engineering purposes - Soil compaction and density tests - Compaction control test - Dry density ratio, moisture variation and moisture ratio

[View on Information Provider website](#)

Abbreviation

AS 1289.5.4.1-1993

Valid from

18/01/1993

Information provider

SAI Global

Author

Standards Australia

Information type

Australian Standard

Format

PDF, Hard copy

Cited By

[This resource is cited by 3 documents \(show Citations\)](#)

Description

This Standard sets out the method for determining the dry density ratio, moisture variation from optimum moisture content and moisture ratio of a soil.

It is applicable to material that contains not more than 20% of material, on a wet basis, retained on the 37.5 mm sieve.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 1289.5.4.1-1993 Methods of testing soils for engineering purposes - Soil compaction and density tests - Compaction control test - Dry density ratio, moisture variation and moisture ratio

This document is CITED BY:

- [AS/NZS 2566.1:1998](#)

AS 1289.5.4.1-1993 is cited by AS/NZS 2566.1:1998 (R2018) Buried Flexible pipelines. Structural Design

- [AS/NZS 2566.2:2002](#)

AS 1289.5.4.1-1993 is cited by AS/NZS 2566.2:2002 (R2016) Buried Flexible pipelines - Installation

- [AS/NZS 3725:2007](#)

AS 1289.5.4.1-1993 is cited by AS/NZS 3725:2007 Design for installation of buried concrete pipes

Back

AS 1289.5.4.1-1993 Methods of testing soils for engineering purposes - Soil compaction and density tests - Compaction control test - Dry density ratio, moisture variation and moisture ratio

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard sets out the method for determining the dry density ratio, moisture variation from optimum moisture content and moisture ratio of a soil.

It is applicable to material that contains not more than 20% of material, on a wet basis, retained on the 37.5 mm sieve.

[View on Information Provider website](#)

[AS 1289.5.4.1-1993 Methods of testing soils for engineering purposes - Soil compaction and density tests - Compaction control test - Dry density ratio, moisture variation and moisture ratio](#)

Description

This Standard sets out the method for determining the dry density ratio, moisture variation from optimum moisture content and moisture ratio of a soil.

It is applicable to material that contains not more than 20% of material, on a wet basis, retained on the 37.5 mm sieve.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS 1289.5.4.1-1993 Methods of testing soils for engineering purposes - Soil compaction and density tests - Compaction control test - Dry density ratio, moisture variation and moisture ratio

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)