

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Print](#) [Save](#) [Email](#)

[Resource detail](#)

[Citations](#)

AS 1289.5.5.1-1998 (R2016) Methods of testing soils for engineering purposes - Soil compaction and density tests - Determination of the minimum and maximum dry density of a cohesionless material - Standard method

[View on Information Provider website](#) [{{ linkText }}](#)

Abbreviation

AS 1289.5.5.1-1998 (R2016)

Valid from

05/03/1998

Information provider

SAI Global

Author

Standards Australia

Information type

Australian Standard

Format

PDF, Hard copy

Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

Description

This method covers the determination of the minimum and maximum dry density of a cohesionless material, using loose pouring to obtain the minimum dry density and vibratory compaction to obtain the maximum dry density.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#) [{{ linkText }}](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 1289.5.5.1-1998 (R2016) Methods of testing soils for engineering purposes - Soil compaction and density tests - Determination of the minimum and maximum dry density of a cohesionless material - Standard method

This document is CITED BY:

- [AS/NZS 2566.2:2002](#)

AS 1289.5.5.1-1998 (R2016) is cited by AS/NZS 2566.2:2002 (R2016) Buried Flexible pipelines - Installation

- [AS/NZS 3725:2007](#)

AS 1289.5.5.1-1998 (R2016) is cited by AS/NZS 3725:2007 Design for installation of buried concrete pipes

Back

AS 1289.5.5.1-1998 (R2016) Methods of testing soils for engineering purposes - Soil compaction and density tests - Determination of the minimum and maximum dry density of a cohesionless material - Standard method

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This method covers the determination of the minimum and maximum dry density of a cohesionless material, using loose pouring to obtain the minimum dry density and vibratory compaction to obtain the maximum dry density.

[View on Information Provider website](#)

[AS 1289.5.5.1-1998 \(R2016\) Methods of testing soils for engineering purposes - Soil compaction and density tests - Determination of the minimum and maximum dry density of a cohesionless material - Standard method](#)

Description

This method covers the determination of the minimum and maximum dry density of a cohesionless material, using loose pouring to obtain the minimum dry density and vibratory compaction to obtain the maximum dry density.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS 1289.5.5.1-1998 (R2016) Methods of testing soils for engineering purposes - Soil compaction and density tests - Determination of the minimum and maximum dry density of a cohesionless material - Standard method

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

--	--	--

--

[Feedback](#)