# Skip to main content Skip to primary navigation Menu • Home Home About this portal Latest updates Print Save Email Resource detail Citations AS 1289.6.3.3-1997 (R2013) <u>View on Information Provider website</u> {{ linkText }} Abbreviation AS 1289.6.3.3-1997 Amendment AS 1289.6.3.3-1997/Amdt No. 1-1999 Valid from 05/06/1997 Information provider SAI Global Author Standards Australia Information type Australian Standard **Format** PDF, Hard copy Cited By This resource is cited by 1 document (show Citations)

### Description

This method sets out the procedure for determining the resistance of a soil to penetration by a flat ended rod of 16 +/-0.2 mm diameter driven with a 9 kg mass, dropping 600 mm.

Use of the method is limited to granular soils with a maximum particle size not exceeding 2 mm, and a layer thickness of at least of 450 mm.

For assistance with locating previous versions, please contact the information provider.

<u>View on Information Provider website</u> {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

# AS 1289.6.3.3-1997 (R2013)

This document is CITED BY:

• AS/NZS 2566.2:2002

Back

# AS 1289.6.3.3-1997 (R2013)

Show what documents this resource is CITED BY

Show what documents this resource CITES

#### Description

This method sets out the procedure for determining the resistance of a soil to penetration by a flat ended rod of 16 +/-0.2 mm diameter driven with a 9 kg mass, dropping 600 mm.

Use of the method is limited to granular soils with a maximum particle size not exceeding 2 mm, and a layer thickness of at least of 450 mm.

View on Information Provider website

## AS 1289.6.3.3-1997 (R2013)

### Description

This method sets out the procedure for determining the resistance of a soil to penetration by a flat ended rod of 16 +/-0.2 mm diameter driven with a 9 kg mass, dropping 600 mm.

Use of the method is limited to granular soils with a maximum particle size not exceeding 2 mm, and a layer thickness of at least of 450 mm.

View on Information Provider website

This resource does not cite any other resources.

# AS 1289.6.3.3-1997 (R2013)

This resource does not CITE any other resources.

Back Close

### **Table of Contents**

Print Save Email Feedback		
	<u>'</u>	
<ul><li>Contact us</li><li>Privacy policy</li><li>Disclaimer</li><li>Copyright</li></ul>		

**Feedback**