

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

AS 1415.4-1984 Unplasticized PVC (UPVC) pipes and fittings for soil, waste and vent (SWV) applications - Part 4: Rubber ring expansion joints

[View on Information Provider website](#)

Abbreviation

AS 1415.4-1984

Valid from

01/01/1984

Information provider

SAI Global

Author

Standards Australia

Information type

New Zealand Standard

Format

Hard copy

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This Standard specifies dimensions, properties and testing for pipes and fittings (moulded and fabricated) in nominal sizes 32 to 150 for use above or below ground in SWV applications. Requirements are included for rubber ring expansion joints for above ground use and fittings for solvent cement jointing. Illustrations of typical fittings are provided.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 1415.4-1984 Unplasticized PVC (UPVC) pipes and fittings for soil, waste and vent (SWV) applications - Part 4: Rubber ring expansion joints

This document is CITED BY:

- [AS 2887-1993](#)

Back

AS 1415.4-1984 Unplasticized PVC (UPVC) pipes and fittings for soil, waste and vent (SWV) applications - Part 4: Rubber ring expansion joints

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard specifies dimensions, properties and testing for pipes and fittings (moulded and fabricated) in nominal sizes 32 to 150 for use above or below ground in SWV applications. Requirements are included for rubber ring expansion joints for above ground use and fittings for solvent cement jointing. Illustrations of typical fittings are provided.

[View on Information Provider website](#)

[AS 1415.4-1984 Unplasticized PVC \(UPVC\) pipes and fittings for soil, waste and vent \(SWV\) applications - Part 4: Rubber ring expansion joints](#)

Description

This Standard specifies dimensions, properties and testing for pipes and fittings (moulded and fabricated) in nominal sizes 32 to 150 for use above or below ground in SWV applications. Requirements are included for rubber ring expansion joints for above ground use and fittings for solvent cement jointing. Illustrations of typical fittings are provided.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS 1415.4-1984 Unplasticized PVC (UPVC) pipes and fittings for soil, waste and vent (SWV) applications - Part 4: Rubber ring expansion joints

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

| | | |
|----------------------|----------------------|----------------------|
| <input type="text"/> | | |
| <input type="text"/> | <input type="text"/> | <input type="text"/> |
| <input type="text"/> | | |

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

| | | |
|----------------------|----------------------|----------------------|
| <input type="text"/> | <input type="text"/> | <input type="text"/> |
| <input type="text"/> | | |

[Feedback](#)