

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Resource detail](#)

[Citations](#)

AS 1462.17-1988 Methods of test for unplasticized PVC (UPVC) pipes and fittings - Method 17: Method for testing pressure pipe joints with elastomeric seals

[View on Information Provider website](#)

Abbreviation

AS 1462.17-1988

Valid from

12/09/1988

Information provider

SAI Global

Author

Standards Australia

Information type

Australian Standard

Format

PDF, Hard copy

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This Standard sets out two methods for pressure testing of unplasticized PVC (UPVC) pipe joints with elastomeric seals for pressure applications, viz a positive internal pressure test (hydrostatic test), and a negative internal/ positive external pressure test (vacuum test). These tests are intended as type tests to demonstrate the adequacy of design and manufacturing process.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 1462.17-1988 Methods of test for unplasticized PVC (UPVC) pipes and fittings - Method 17: Method for testing pressure pipe joints with elastomeric seals

This document is CITED BY:

- [AS/NZS 1477:2006](#)

AS 1462.17-1988 is cited by AS/NZS 1477:2006 PVC pipes and fittings for pressure applications

Back

AS 1462.17-1988 Methods of test for unplasticized PVC (UPVC) pipes and fittings - Method 17: Method for testing pressure pipe joints with elastomeric seals

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard sets out two methods for pressure testing of unplasticized PVC (UPVC) pipe joints with elastomeric seals for pressure applications, viz a positive internal pressure test (hydrostatic test), and a negative internal/ positive external pressure test (vacuum test). These tests are intended as type tests to demonstrate the adequacy of design and manufacturing process.

[View on Information Provider website](#)

[AS 1462.17-1988 Methods of test for unplasticized PVC \(UPVC\) pipes and fittings - Method 17: Method for testing pressure pipe joints with elastomeric seals](#)

Description

This Standard sets out two methods for pressure testing of unplasticized PVC (UPVC) pipe joints with elastomeric seals for pressure applications, viz a positive internal pressure test (hydrostatic test), and a negative internal/ positive external pressure test (vacuum test). These tests are intended as type tests to demonstrate the adequacy of design and manufacturing process.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS 1462.17-1988 Methods of test for unplasticized PVC (UPVC) pipes and fittings - Method 17: Method for testing pressure pipe joints with elastomeric seals

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

--	--	--

--

[Feedback](#)