

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  

[Save](#)

[Resource detail](#)

[Citations](#)

## AS 1464.1-1984 and AS 1464.2-1984 Plastics pipes and fittings for gas reticulation - Unplasticized PVC (UPVC) - Part 1: Pipes - Part 2: Fittings

[View on Information Provider website](#)

### Abbreviation

AS 1464.1-1984 and AS 1464.2-1984

### Valid from

11/05/1984

---

### Information provider

SAI Global

### Author

Standards Australia

### Information type

Australian Standard

### Format

PDF, Hard copy

---

### Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

---

### Description

This standard specifies requirements for UPVC pipes for use in gas mains and services for direct burial and refiner applications. Such pipe is intended for use with natural gas, liquified petroleum gas (LP gas), and air and LP gas mixtures at pressures up to 450 kPa.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## AS 1464.1-1984 and AS 1464.2-1984 Plastics pipes and fittings for gas reticulation - Unplasticized PVC (UPVC) - Part 1: Pipes - Part 2: Fittings

This document is CITED BY:

- [AS/NZS 5601.1:2013](#)

AS 1464.1-1984 and AS 1464.2-1984 is cited by AS/NZS 5601.1:2013 Gas installations - General installations

- [NZS 5261:2003](#)

AS 1464.1-1984 and AS 1464.2-1984 is cited by NZS 5261:2003 Gas installation

Back

## AS 1464.1-1984 and AS 1464.2-1984 Plastics pipes and fittings for gas reticulation - Unplasticized PVC (UPVC) - Part 1: Pipes - Part 2: Fittings

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

This standard specifies requirements for UPVC pipes for use in gas mains and services for direct burial and refiner applications. Such pipe is intended for use with natural gas, liquified petroleum gas (LP gas), and air and LP gas mixtures at pressures up to 450 kPa.

[View on Information Provider website](#)

[AS 1464.1-1984 and AS 1464.2-1984 Plastics pipes and fittings for gas reticulation - Unplasticized PVC \(UPVC\) - Part 1: Pipes - Part 2: Fittings](#)

### Description

This standard specifies requirements for UPVC pipes for use in gas mains and services for direct burial and refiner applications. Such pipe is intended for use with natural gas, liquified petroleum gas (LP gas), and air and LP gas mixtures at pressures up to 450 kPa.

[View on Information Provider website](#)

This resource does not cite any other resources.

## AS 1464.1-1984 and AS 1464.2-1984 Plastics pipes and fittings for gas reticulation - Unplasticized PVC (UPVC) - Part 1: Pipes - Part 2: Fittings

This resource does not CITE any other resources.

Back

Close

### Table of Contents

Print [Save](#) Email

[Feedback](#)

  


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)