

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

AS 1523-1981 Elastomeric bearings for use in structures

[View on Information Provider website](#)

Abbreviation
AS 1523-1981
Valid from
01/01/1981

Information provider
SAI Global
Author
Standards Australia
Information type
Australian Standard
Format
PDF

Cited By
[This resource is cited by 2 documents \(show Citations\)](#)

Description

This standard specifies the dimensional and performance characteristics and acceptance tests for a range of laminated rectangular and circular bearings manufactured from natural rubber for use in structures.

It covers a range of laminated and rectangular bearings manufactured from natural rubber, ranging in capacity from 280 to 9000 kN.

Tables set out dimensions and predicted performances for the bearings, and appendices give the background to the design method used in calculation of the tables.

Methods of test for the bearings are also included in an appendix together with acceptance criteria for completed bearings.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 1523-1981 Elastomeric bearings for use in structures

This document is CITED BY:

- [NZS 3112.1:1986](#)

AS 1523-1981 is cited by NZS 3112.1:1986 Methods of test for concrete - Tests relating to fresh concrete

- [NZS 3112.2:1986](#)

AS 1523-1981 is cited by NZS 3112.2:1986 Methods of test for concrete - Tests relating to the determination of strength of concrete

Back

AS 1523-1981 Elastomeric bearings for use in structures

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This standard specifies the dimensional and performance characteristics and acceptance tests for a range of laminated rectangular and circular bearings manufactured from natural rubber for use in structures.

It covers a range of laminated and rectangular bearings manufactured from natural rubber, ranging in capacity from 280 to 9000 kN.

Tables set out dimensions and predicted performances for the bearings, and appendices give the background to the design method used in calculation of the tables.

Methods of test for the bearings are also included in an appendix together with acceptance criteria for completed bearings.

[View on Information Provider website](#)

[AS 1523-1981 Elastomeric bearings for use in structures](#)

Description

This standard specifies the dimensional and performance characteristics and acceptance tests for a range of laminated rectangular and circular bearings manufactured from natural rubber for use in structures.

It covers a range of laminated and rectangular bearings manufactured from natural rubber, ranging in capacity from 280 to 9000 kN.

Tables set out dimensions and predicted performances for the bearings, and appendices give the background to the design method used in calculation of the tables.

Methods of test for the bearings are also included in an appendix together with acceptance criteria for completed bearings.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS 1523-1981 Elastomeric bearings for use in structures

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)