

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

AS 1580.409.1-2002 (R2013) Paints and related materials - Methods of test - Resistance to mudcracking

[View on Information Provider website](#)

Abbreviation

AS 1580.409.1-2002 (R2013)

Valid from

13/12/2002

Replaces

Information provider

SAI Global

Author

Standards Australia

Information type

Australian Standard

Format

PDF, Hard copy

Cited By

[This resource is cited by 4 documents \(show Citations\)](#)

Description

This Standard sets out a method for determining the resistance to mudcracking of an air-dried latex paint film, typically applied at 30–50 mm dry film thickness.

It provides a method for evaluating the tendency of paint coatings to crack in locations where there has been an excessive build-up of paint, e.g. in the corner of a room, particularly at ceilings and cornices, which occurs most commonly with flat paints.

Scope

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 1580.409.1-2002 (R2013) Paints and related materials - Methods of test - Resistance to mudcracking

This document is CITED BY:

- [AS 3730.10-2006](#)

AS 1580.409.1-2002 (R2013) is cited by AS 3730.10-2006 (R2016) Guide to the properties of paints for buildings. Part 10: Latex - Exterior - Gloss

- [AS 3730.7-2006 \(R2016\)](#)

AS 1580.409.1-2002 (R2013) is cited by AS 3730.7-2006 (R2016) Guide to the properties of paints for buildings. Part 7: Latex - Exterior - Flat

- [AS 3730.8-2006 \(R2016\)](#)

AS 1580.409.1-2002 (R2013) is cited by AS 3730.8-2006 (R2016) Guide to the properties of paints for buildings. Part 8: Latex - Exterior - Low-gloss

- [AS 3730.9-2006 \(R2016\)](#)

AS 1580.409.1-2002 (R2013) is cited by AS 3730.9-2006 (R2016) Guide to the properties of paints for buildings. Part 9: Latex - Exterior - Semi-gloss

[Back](#)

AS 1580.409.1-2002 (R2013) Paints and related materials - Methods of test - Resistance to mudcracking

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard sets out a method for determining the resistance to mudcracking of an air-dried latex paint film, typically applied at 30–50 mm dry film thickness.

It provides a method for evaluating the tendency of paint coatings to crack in locations where there has been an excessive build-up of paint, e.g. in the corner of a room, particularly at ceilings and cornices, which occurs most commonly with flat paints.

[View on Information Provider website](#)

[AS 1580.409.1-2002 \(R2013\) Paints and related materials - Methods of test - Resistance to mudcracking](#)

Description

This Standard sets out a method for determining the resistance to mudcracking of an air-dried latex paint film, typically applied at 30–50 mm dry film thickness.

It provides a method for evaluating the tendency of paint coatings to crack in locations where there has been an excessive build-up of paint, e.g. in the corner of a room, particularly at ceilings and cornices, which occurs most commonly with flat paints.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS 1580.409.1-2002 (R2013) Paints and related materials - Methods of test - Resistance to mudcracking

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)