Skip to main content Skip to primary navigation
Menu
Home Home About this contains
About this portal About this portal
Latest updates
Print Save Email
Resource detail
<u>Citations</u>
AS 1617.4-1993 Refractory bricks and shapes Silica
View on Information Provider website {{ linkText }}
Abbreviation
AS 1617.4-1993
Amendment
AS 1617.4-1993/Amdt 1-1994
Valid from
15/11/1993
Replaces
Information provider
SAI Global
Author
Standards Australia
Information type
Australian Standard
Format
PDF, Hard copy
Cited By This resource is cited by 1 document (show Citations)
Description
This Standard specifies requirements for refractory bricks and shapes having a maximum free quartz content of
5 percent by mass and produced essentially from silcrete, quartzite and ganister.
It applies to machine-made silica refractory bricks and shapes used principally in the glass and steel industries.
Scope
For assistance with locating previous versions, please contact the information provider.
and the state of t
View on Information Provider website {{ linkText }}
For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 1617.4-1993 Refractory bricks and shapes Silica

This document is CITED BY:

AS/NZS 3869:1999

AS 1617.4-1993 is cited by AS/NZS 3869:1999 Domestic solid fuel burning appliances - Design and construction



AS 1617.4-1993 Refractory bricks and shapes Silica

Show what documents this resource is CITED BY Show what documents this resource CITES

Description

This Standard specifies requirements for refractory bricks and shapes having a maximum free quartz content of 5 percent by mass and produced essentially from silcrete, quartzite and ganister.

It applies to machine-made silica refractory bricks and shapes used principally in the glass and steel industries.

View on Information Provider website

AS 1617.4-1993 Refractory bricks and shapes Silica

Description

This Standard specifies requirements for refractory bricks and shapes having a maximum free quartz content of 5 percent by mass and produced essentially from silcrete, quartzite and ganister.

It applies to machine-made silica refractory bricks and shapes used principally in the glass and steel industries.

View on Information Provider website

This resource does not cite any other resources.

AS 1617.4-1993 Refractory bricks and shapes Silica

This resource does not CITE any other resources.



Table of Contents

Print Save Email		
<u>Feedback</u>		

- Contact us
- Privacy policy
- Disclaimer
- Copyright

	_	·	

<u>Feedback</u>