

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  

[Save](#)

[Resource detail](#)  
[Citations](#)

## AS 1910-2004 (R2016) Water supply - Float control valves for use in hot and cold water

[View on Information Provider website](#)

### Abbreviation

AS 1910-2004

### Amendment

AS 1910-2004 (R2016)/Amdt 1-2006 incorporated, published 20/07/2006

### Valid from

07/07/2004

---

### Information provider

SAI Global

### Author

Standards Australia

### Information type

Australian Standard

### Format

PDF, Hard copy

---

### Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

---

### Description

This Standard specifies requirements for active float control valves for use in water supply systems where the normal working temperature does not exceed 95°C and the continuous working pressure extends up to a maximum of 1.4 MPa for a range of nominal sizes from DN 6 to DN 80.

### Scope

This Standard does not cover WC cistern flushing valves.

**Note:** WC cistern flushing valves are covered in all parts of AS 1172.

Means of demonstrating compliance with this Standard are set out in Appendix A.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## AS 1910-2004 (R2016) Water supply - Float control valves for use in hot and cold water

This document is CITED BY:

- [AS/NZS 3500.4:2015](#)

AS 1910-2004 is cited by AS/NZS 3500.4:2015 Plumbing and drainage - Heated water services

- [AS/NZS 3500.4:2018](#)

AS 1910-2004 is cited by AS/NZS 3500.4:2018 Plumbing and drainage Part 4: Heated water services

Back

## AS 1910-2004 (R2016) Water supply - Float control valves for use in hot and cold water

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

This Standard specifies requirements for active float control valves for use in water supply systems where the normal working temperature does not exceed 95°C and the continuous working pressure extends up to a maximum of 1.4 MPa for a range of nominal sizes from DN 6 to DN 80.

[View on Information Provider website](#)

[AS 1910-2004 \(R2016\) Water supply - Float control valves for use in hot and cold water](#)

### Description

This Standard specifies requirements for active float control valves for use in water supply systems where the normal working temperature does not exceed 95°C and the continuous working pressure extends up to a maximum of 1.4 MPa for a range of nominal sizes from DN 6 to DN 80.

[View on Information Provider website](#)

This resource does not cite any other resources.

## AS 1910-2004 (R2016) Water supply - Float control valves for use in hot and cold water

This resource does not CITE any other resources.

Back

Close

### Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)