Skip to main content Skip to primary navigation Menu Menu
 Home Home About this portal Latest updates
Print Save Email Resource detail
AS 2944.1-2007 Plastics pipes and fittings for gas reticulation - Part 1
Polyamide pipes View on Information Provider website {{ linkText }}
Abbreviation AS 2944.1-2007 Valid from

Information provider

SAI Global

Author

Standards Australia

Information type

Australian Standard

Format

PDF

Cited By

This resource is cited by 2 documents (show Citations)

Description

This Standard specifies requirements for polyamide pipes for use in gas mains and services for direct burial and reliner applications. Such pipes are intended for use in the distribution of natural gas, manufactured gas, liquefied petroleum gas (LPG) and LPG/air mixtures at pressures up to 400 kPa.

For assistance with locating previous versions, please contact the information provider.

<u>View on Information Provider website</u> {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 2944.1-2007 Plastics pipes and fittings for gas reticulation - Part 1: Polyamide pipes

This document is CITED BY:

AS/NZS 5601.1:2010

AS/NZS 5601.1:2013

AS 2944.1-2007 is cited by AS/NZS 5601.1:2013 Gas installations - General installations

Back

AS 2944.1-2007 Plastics pipes and fittings for gas reticulation - Part 1: Polyamide pipes

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard specifies requirements for polyamide pipes for use in gas mains and services for direct burial and reliner applications. Such pipes are intended for use in the distribution of natural gas, manufactured gas, liquefied petroleum gas (LPG) and LPG/air mixtures at pressures up to 400 kPa.

View on Information Provider website

AS 2944.1-2007 Plastics pipes and fittings for gas reticulation - Part 1: Polyamide pipes

Description

This Standard specifies requirements for polyamide pipes for use in gas mains and services for direct burial and reliner applications. Such pipes are intended for use in the distribution of natural gas, manufactured gas, liquefied petroleum gas (LPG) and LPG/air mixtures at pressures up to 400 kPa.

View on Information Provider website

This resource does not cite any other resources.

AS 2944.1-2007 Plastics pipes and fittings for gas reticulation - Part 1: Polyamide pipes

This resource does not CITE any other resources.



Table of Contents

Print Save Email Feedback		
Contact usPrivacy policyDisclaimer		

Feedback

Copyright