

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

AS 3517-2007 (R2018) Capillary fittings of copper and copper alloy for non-pressure sanitary plumbing applications

[View on Information Provider website](#)

Abbreviation

AS 3517-2007

Valid from

08/06/2007

Replaces

Information provider

SAI Global

Author

Standards Australia

Information type

Australian Standard

Format

PDF

Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

Description

This Standard specifies requirements for copper and copper alloy capillary fittings for use in non-pressure sanitary plumbing applications with tubes complying with AS 1432 and AS 3795 in the range of nominal sizes from DN 32 to DN 225. It covers cast, hot-pressed, shell-moulded, and tubular fittings with socket/spigot capillary connection ends.

Scope

This Standard does not apply to fittings for use in pressure applications, including pumping mains and flushing systems in sanitary plumbing systems (see AS 3688), nor to waste fittings (see AS 1589).

Illustrations used in this Standard are diagrammatic only and have been chosen without prejudice.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 3517-2007 (R2018) Capillary fittings of copper and copper alloy for non-pressure sanitary plumbing applications

This document is CITED BY:

- [AS/NZS 3500.2:2015](#)

AS 3517-2007 is cited by AS/NZS 3500.2:2015 Plumbing and drainage - Part 2: Sanitary plumbing and drainage

- [AS/NZS 3500.2:2018](#)

AS 3517-2007 is cited by AS/NZS 3500.2:2018 Plumbing and drainage Part 2: Sanitary plumbing and drainage

Back

AS 3517-2007 (R2018) Capillary fittings of copper and copper alloy for non-pressure sanitary plumbing applications

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard specifies requirements for copper and copper alloy capillary fittings for use in non-pressure sanitary plumbing applications with tubes complying with AS 1432 and AS 3795 in the range of nominal sizes from DN 32 to DN 225. It covers cast, hot-pressed, shell-moulded, and tubular fittings with socket/spigot capillary connection ends.

[View on Information Provider website](#)

[AS 3517-2007 \(R2018\) Capillary fittings of copper and copper alloy for non-pressure sanitary plumbing applications](#)

Description

This Standard specifies requirements for copper and copper alloy capillary fittings for use in non-pressure sanitary plumbing applications with tubes complying with AS 1432 and AS 3795 in the range of nominal sizes from DN 32 to DN 225. It covers cast, hot-pressed, shell-moulded, and tubular fittings with socket/spigot capillary connection ends.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS 3517-2007 (R2018) Capillary fittings of copper and copper alloy for non-pressure sanitary plumbing applications

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)

- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)