

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

AS 3718-1992 Water supply - Metal-bodied taps - Specified by performance

[View on Information Provider website](#)

Abbreviation
AS 3718-1992
Valid from
17/08/1992

Information provider
SAI Global
Author
Standards Australia
Information type
Australian Standard
Format
PDF

Cited By
[This resource is cited by 1 document \(show Citations\)](#)

Description

This Standard specifies requirements for metal-bodied draw-off taps, mixing taps mechanical (non-thermostatic) and delivery taps in the range of nominal sizes from DN 6 to DN 50 inclusive with continuous working pressures not exceeding 1.4 MPa and continuous operating temperatures not exceeding 80° Celsius.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 3718-1992 Water supply - Metal-bodied taps - Specified by performance

This document is CITED BY:

- [AS/NZS 2023:1995](#)

AS 3718-1992 is cited by AS/NZS 2023:1995 Baths for ablutionary purposes

Back

AS 3718-1992 Water supply - Metal-bodied taps - Specified by performance

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard specifies requirements for metal-bodied draw-off taps, mixing taps mechanical (non-thermostatic) and delivery taps in the range of nominal sizes from DN 6 to DN 50 inclusive with continuous working pressures not exceeding 1.4 MPa and continuous operating temperatures not exceeding 80° Celsius.

[View on Information Provider website](#)

[AS 3718-1992 Water supply - Metal-bodied taps - Specified by performance](#)

Description

This Standard specifies requirements for metal-bodied draw-off taps, mixing taps mechanical (non-thermostatic) and delivery taps in the range of nominal sizes from DN 6 to DN 50 inclusive with continuous working pressures not exceeding 1.4 MPa and continuous operating temperatures not exceeding 80° Celsius.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS 3718-1992 Water supply - Metal-bodied taps - Specified by performance

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)