

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

AS 3730.14-2006 (R2016) Guide to the properties of paints for buildings. Part 14: Undercoat - Solvent-borne - Interior/exterior

[View on Information Provider website](#)

Abbreviation

AS 3730.14-2006

Valid from

02/02/2006

Information provider

SAI Global

Author

Standards Australia

Information type

Australian Standard

Format

PDF

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This document provides a guide to the features and typical characteristics that are expected of a solvent-borne undercoat for interior and exterior use, when applied by brush, roller or spray in accordance with the manufacturer's instructions.

Paints covered by this Standard are classified as paint Type B17 of AS/NZS 2311.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 3730.14-2006 (R2016) Guide to the properties of paints for buildings. Part 14: Undercoat - Solvent-borne - Interior/exterior

This document is CITED BY:

- [AS 3730.6-2006 \(R2016\)](#)

AS 3730.14-2006 is cited by AS 3730.6-2006 (R2016) Guide to the properties of paints for buildings. Part 6: Solvent-borne - Exterior - Full gloss enamel

Back

AS 3730.14-2006 (R2016) Guide to the properties of paints for buildings. Part 14: Undercoat - Solvent-borne - Interior/exterior

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This document provides a guide to the features and typical characteristics that are expected of a solvent-borne undercoat for interior and exterior use, when applied by brush, roller or spray in accordance with the manufacturer's instructions.

Paints covered by this Standard are classified as paint Type B17 of AS/NZS 2311.

[View on Information Provider website](#)

[AS 3730.14-2006 \(R2016\) Guide to the properties of paints for buildings. Part 14: Undercoat - Solvent-borne - Interior/exterior](#)

Description

This document provides a guide to the features and typical characteristics that are expected of a solvent-borne undercoat for interior and exterior use, when applied by brush, roller or spray in accordance with the manufacturer's instructions.

Paints covered by this Standard are classified as paint Type B17 of AS/NZS 2311.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS 3730.14-2006 (R2016) Guide to the properties of paints for buildings. Part 14: Undercoat - Solvent-borne - Interior/exterior

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

