

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

AS 3730.6-2006 (R2016) Guide to the properties of paints for buildings. Part 6: Solvent-borne - Exterior - Full gloss enamel

[View on Information Provider website](#)

Abbreviation

AS 3730.6-2006 (R2016)

Valid from

30/01/2006

Information provider

SAI Global

Author

Standards Australia

Information type

Australian Standard

Format

PDF

Cited By

[This resource is cited by 7 documents \(show Citations\)](#)

Cites

[This resource cites 37 documents \(show Citations\)](#)

Description

This Standard provides a guide to the features and typical characteristics that are expected of a solvent-borne interior/exterior full gloss enamel finish when applied by brush, roller or spray, in accordance with the manufacturers instructions. Paints covered by this guide are classified as Paint Type B5 of AS/NZS 2311.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 3730.6-2006 (R2016) Guide to the properties of paints for buildings. Part 6: Solvent-borne - Exterior - Full gloss enamel

This document is CITED BY:

- [E2/AS1 \(Third Edition, Amendment 7\)](#)

AS 3730.6-2006 (R2016) is cited by Acceptable Solution E2/AS1: External Moisture from 01/08/2011

- [E2/AS1 \(Third Edition, Amendment 5\)](#)

AS 3730.6-2006 (R2016) is cited by Acceptable Solution E2/AS1: External Moisture from 01/08/2011

- [E2/AS1 \(Third Edition, Amendment 6\)](#)

AS 3730.6-2006 (R2016) is cited by Acceptable Solution E2/AS1: External Moisture from 01/08/2011

- [E2/AS1 \(Third Edition, Amendment 8\)](#)

AS 3730.6-2006 (R2016) is cited by Acceptable Solution E2/AS1: External Moisture from 01/08/2011

- [E2/AS1 \(Third Edition, Amendment 5, Errata 2\)](#)

AS 3730.6-2006 (R2016) is cited by Acceptable Solution E2/AS1: External Moisture from 01/08/2011

- [E2/AS1 \(Third Edition, Amendment 9\)](#)

AS 3730.6-2006 (R2016) is cited by Acceptable Solution E2/AS1: External Moisture from 01/08/2011

- [NASH Building Envelope Solutions: 2019](#)

AS 3730.6-2006 (R2016) is cited by NASH Building Envelope Solutions: 2019 - Light Steel Framed Buildings.

Back

AS 3730.6-2006 (R2016) Guide to the properties of paints for buildings. Part 6: Solvent-borne - Exterior - Full gloss enamel

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard provides a guide to the features and typical characteristics that are expected of a solvent-borne interior/exterior full gloss enamel finish when applied by brush, roller or spray, in accordance with the manufacturers instructions. Paints covered by this guide are classified as Paint Type B5 of AS/NZS 2311.

[View on Information Provider website](#)

[AS 3730.6-2006 \(R2016\) Guide to the properties of paints for buildings. Part 6: Solvent-borne - Exterior - Full gloss enamel](#)

Description

This Standard provides a guide to the features and typical characteristics that are expected of a solvent-borne interior/exterior full gloss enamel finish when applied by brush, roller or spray, in accordance with the manufacturers instructions. Paints covered by this guide are classified as Paint Type B5 of AS/NZS 2311.

[View on Information Provider website](#)

This resource cites:

AS 3730.6-2006 (R2016) Guide to the properties of paints for buildings. Part 6: Solvent-borne - Exterior - Full gloss enamel

This document CITES:

New Zealand Standards

- [AS/NZS 1580.101.1:1999 \(R2013\)](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.101.1:1999 (R2013) Paints and related materials - Methods of test - Method 101.1: Conditions of test - Temperature, humidity and airflow control

- [AS/NZS 1580.101.5:1999 \(R2013\)](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.101.5:1999 (R2013) Paints and related materials - Methods of test - Method 101.5: Conditions of test - Temperature and humidity control

- [AS/NZS 1580.103.1:1995 \(R2013\)](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.103.1:1995 (R2013) Paints and related materials - Methods of test - Examination and preparation of samples for testing

- [AS/NZS 1580.104.1:2000 \(R2013\)](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.104.1:2000 (R2013) Paints and related materials - Methods of test - Method 104.1: Recommended materials for test panels

- [AS/NZS 1580.204.1:1998 \(R2013\)](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.204.1:1998 (R2013) Paints and related materials - Methods of test - Method 204.1: Fineness of grind

- [AS/NZS 1580.205.1:1997](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.205.1:1997 (R2013) Paints and related materials - Methods of test - Method 205.1: Application properties - Brushing

- [AS/NZS 1580.205.2:1997](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.205.2:1997 (R2013) Paints and related materials - Methods of test - Method 205.2: Application properties - Conventional spraying

- [AS/NZS 1580.205.3:1997](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.205.3:1997 (R2013) Paints and related materials - Methods of test - Method 205.3: Application properties - Roller coating

- [AS/NZS 1580.205.4:1998](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.205.4:1998 (R2013) Paints and related materials - Methods of test - Method 205.4: Application properties - Airless spraying

- [AS/NZS 1580.211.1:1995](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.211.1:1995 (R2013) Paints and related materials - Methods of test - Method 211.1: Degree of settling

- [AS/NZS 1580.211.2:1995](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.211.2:1995 (R2013) Paints and related materials - Methods of test - Method 211.2: Ease of manual re-incorporation

- [AS/NZS 1580.213.1:1997 \(R2013\)](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.213.1:1997 (R2013) Paints and related materials - Methods of test - Method 213.1: Relative dry hiding power

- [AS/NZS 1580.214.0:1996 \(R2013\)](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.214.0:1996 (R2013) Paints and related materials - Methods of test - Method 214.0: Rheological properties - Guide to test methods

- [AS/NZS 1580.457.1:1996](#)

AS 3730.6-2006 (R2016) cites AS/NZS 1580.457.1:1996 (R2013) Methods of test for paints and related materials - Resistance to natural weathering

- [AS/NZS 1580.461.1:1995 \(R2013\)](#)
AS 3730.6-2006 (R2016) cites AS/NZS 1580.461.1:1995 (R2013) Methods of test for paints and related materials - Method 461.1: Determination of resistance to yellowing (dark chamber)
- [AS/NZS 1580.481.1.10:1998 \(Reconfirmed in 2013\)](#)
AS 3730.6-2006 (R2016) cites AS/NZS 1580.481.1.10:1998 (R2013) Methods of test for paints and related materials - Exposed to weathering - Degree of flaking and peeling
- [AS/NZS 1580.481.1.11:1998 \(Reconfirmed in 2013\)](#)
AS 3730.6-2006 (R2016) cites AS/NZS 1580.481.1.11:1998 (R2013) Methods of test for paints and related materials - Exposed to weathering - Degree of chalking
- [AS/NZS 1580.481.1.12:1998 \(R2013\)](#)
AS 3730.6-2006 (R2016) cites AS/NZS 1580.481.1.12:1998 (R2013) Paints and related materials - Methods of test Coatings - Method 481.1.12: Exposed to weathering - Degree of colour change
- [AS/NZS 1580.481.1.2:1998 \(R2013\)](#)
AS 3730.6-2006 (R2016) cites AS/NZS 1580.481.1.2:1998 (R2013) Paints and related materials - Methods of test Coatings - Method 481.1.2: Exposed to weathering - Discolouration (including bronzing)
- [AS/NZS 1580.481.1.5:1999 \(Reconfirmed in 2013\)](#)
AS 3730.6-2006 (R2016) cites AS/NZS 1580.481.1.5:1999 (R2013) Methods of test for paints and related materials - Exposed to weathering - Change in gloss
- [AS/NZS 1580.481.1.7:1998 \(Reconfirmed in 2013\)](#)
AS 3730.6-2006 (R2016) cites AS/NZS 1580.481.1.7:1998 (R2013) Methods of test for paints and related materials - Exposed to weathering - Degree of checking
- [AS/NZS 1580.481.1.8:1998 \(Reconfirmed in 2013\)](#)
AS 3730.6-2006 (R2016) cites AS/NZS 1580.481.1.8:1998 (R2013) Methods of test for paints and related materials - Exposed to weathering - Degree of cracking
- [AS/NZS 1580.481.1.9:1998 \(Reconfirmed in 2013\)](#)
AS 3730.6-2006 (R2016) cites AS/NZS 1580.481.1.9:1998 (R2013) Methods of test for paints and related materials - Exposed to weathering - Degree of blistering
- [AS/NZS 1580.601.1:1995](#)
AS 3730.6-2006 (R2016) cites AS/NZS 1580.601.1:1995 (R2013) Methods of test for paints and related materials - Colour - Visual comparison
- [AS/NZS 1580.602.2:1995 \(R2013\)](#)
AS 3730.6-2006 (R2016) cites AS/NZS 1580.602.2:1995 (R2013) Paints and related materials - Methods of test - - Measurement of specular gloss of non-metallic paint films at 20 degrees, 60 degrees and 85 degrees
- [AS/NZS 2310:2002](#)
AS 3730.6-2006 (R2016) cites AS/NZS 2310:2002 (R2016) Glossary of paint and painting terms
- [AS/NZS 2311:2000](#)
AS 3730.6-2006 (R2016) cites AS/NZS 2311:2000 Guide to the painting of buildings

Australian Standards

- [AS 1580.203.1-2004](#)
AS 3730.6-2006 (R2016) cites AS 1580.203.1-2004 Paints and related materials - Methods of test - Method 203.1: Skin

formation

- [AS 1580.213.2-2004](#)

AS 3730.6-2006 (R2016) cites AS 1580.213.2-2004 Paints and related materials - Methods of test - Method 213.2: Dry hiding power - Contrast ratio

- [AS 1580.301.2-1990](#)

AS 3730.6-2006 (R2016) cites AS 1580.301.2-1990 (R2013) Paints and related materials - Methods of test - Method 301.2: Non-volatile content by volume (volume solids)

- [AS 1580.401.3-2002 \(R2013\)](#)

AS 3730.6-2006 (R2016) cites AS 1580.401.3-2002 (R2013) Paints and related materials - Methods of test - Method 401.3: Drying times using a BK-type recorder

- [AS 1580.603.1-2002](#)

AS 3730.6-2006 (R2016) cites AS 1580.603.1-2002 (R2013) Paints and related materials - Methods of test - Method 603.1: Finish - General appearance

- [AS 2700-1996](#)

AS 3730.6-2006 (R2016) cites AS 2700-1996 Colour Standards for general purposes

- [AS 3730.0-2006 \(R2016\)](#)

AS 3730.6-2006 (R2016) cites AS 3730.0-2006 (R2016) Guide to the properties of paints for buildings - Part 0: General information on the specification, purchasing and testing of paints

- [AS 3730.10-2006](#)

AS 3730.6-2006 (R2016) cites AS 3730.10-2006 (R2016) Guide to the properties of paints for buildings. Part 10: Latex - Exterior - Gloss

- [AS 3730.14-2006](#)

AS 3730.6-2006 (R2016) cites AS 3730.14-2006 (R2016) Guide to the properties of paints for buildings. Part 14: Undercoat - Solvent-borne - Interior/exterior

Other

- [The Poisons Standard \(the SUSMP\)](#)

AS 3730.6-2006 (R2016) cites The Poisons Standard (Standard for the Uniform Scheduling of Medicines and Poisons - SUSMP)

[Back](#)

[Close](#)

Table of Contents

[Print](#)

[Save](#)

[Email](#)

[Feedback](#)

<input type="text"/>		
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

--	--	--

--

[Feedback](#)