

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

AS 3730.7-2006 (R2016) Guide to the properties of paints for buildings. Part 7: Latex - Exterior - Flat

[View on Information Provider website](#)

Abbreviation

AS 3730.7-2006 (R2016)

Valid from

07/04/2006

Information provider

SAI Global

Author

Standards Australia

Information type

Australian Standard

Format

PDF

Cited By

[This resource is cited by 8 documents \(show Citations\)](#)

Cites

[This resource cites 33 documents \(show Citations\)](#)

Description

This Standard provides a guide to the features and typical characteristics that are expected of a latex flat finish paint, intended primarily for exterior use, when applied by brush, roller or sprayer in accordance with the manufacturers instructions.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 3730.7-2006 (R2016) Guide to the properties of paints for buildings. Part 7: Latex - Exterior - Flat

This document is CITED BY:

- [E2/AS1 \(Third Edition, Amendment 5, Errata 2\)](#)

AS 3730.7-2006 (R2016) is cited by Acceptable Solution E2/AS1: External Moisture from 01/08/2011

- [E2/AS1 \(Third Edition, Amendment 9\)](#)

AS 3730.7-2006 (R2016) is cited by Acceptable Solution E2/AS1: External Moisture from 01/08/2011

- [E2/AS1 \(Third Edition, Amendment 7\)](#)

AS 3730.7-2006 (R2016) is cited by Acceptable Solution E2/AS1: External Moisture from 01/08/2011

- [E2/AS1 \(Third Edition, Amendment 5\)](#)

AS 3730.7-2006 (R2016) is cited by Acceptable Solution E2/AS1: External Moisture from 01/08/2011

- [E2/AS1 \(Third Edition, Amendment 6\)](#)

AS 3730.7-2006 (R2016) is cited by Acceptable Solution E2/AS1: External Moisture from 01/08/2011

- [E2/AS1 \(Third Edition, Amendment 8\)](#)

AS 3730.7-2006 (R2016) is cited by Acceptable Solution E2/AS1: External Moisture from 01/08/2011

- [NASH Building Envelope Solutions: 2019](#)

AS 3730.7-2006 (R2016) is cited by NASH Building Envelope Solutions: 2019 - Light Steel Framed Buildings.

- [NZS 4251.1:2007](#)

AS 3730.7-2006 (R2016) is cited by NZS 4251.1:2007 Solid plastering - Cement plaster for walls, ceilings and soffits

Back

AS 3730.7-2006 (R2016) Guide to the properties of paints for buildings. Part 7: Latex - Exterior - Flat

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard provides a guide to the features and typical characteristics that are expected of a latex flat finish paint, intended primarily for exterior use, when applied by brush, roller or sprayer in accordance with the manufacturers instructions.

[View on Information Provider website](#)

[AS 3730.7-2006 \(R2016\) Guide to the properties of paints for buildings. Part 7: Latex - Exterior - Flat](#)

Description

This Standard provides a guide to the features and typical characteristics that are expected of a latex flat finish paint, intended primarily for exterior use, when applied by brush, roller or sprayer in accordance with the manufacturers instructions.

[View on Information Provider website](#)

This resource cites:

AS 3730.7-2006 (R2016) Guide to the properties of paints for buildings. Part 7: Latex - Exterior - Flat

This document CITES:

New Zealand Standards

- [AS/NZS 1580.101.1:1999 \(R2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.101.1:1999 (R2013) Paints and related materials - Methods of test - Method 101.1: Conditions of test - Temperature, humidity and airflow control

- [AS/NZS 1580.101.5:1999 \(R2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.101.5:1999 (R2013) Paints and related materials - Methods of test - Method 101.5: Conditions of test - Temperature and humidity control

- [AS/NZS 1580.103.1:1995 \(R2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.103.1:1995 (R2013) Paints and related materials - Methods of test - Examination and preparation of samples for testing

- [AS/NZS 1580.104.1:2000 \(R2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.104.1:2000 (R2013) Paints and related materials - Methods of test - Method 104.1: Recommended materials for test panels

- [AS/NZS 1580.204.1:1998 \(R2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.204.1:1998 (R2013) Paints and related materials - Methods of test - Method 204.1: Fineness of grind

- [AS/NZS 1580.205.1:1997](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.205.1:1997 (R2013) Paints and related materials - Methods of test - Method 205.1: Application properties - Brushing

- [AS/NZS 1580.205.2:1997](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.205.2:1997 (R2013) Paints and related materials - Methods of test - Method 205.2: Application properties - Conventional spraying

- [AS/NZS 1580.205.3:1997](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.205.3:1997 (R2013) Paints and related materials - Methods of test - Method 205.3: Application properties - Roller coating

- [AS/NZS 1580.205.4:1998](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.205.4:1998 (R2013) Paints and related materials - Methods of test - Method 205.4: Application properties - Airless spraying

- [AS/NZS 1580.211.1:1995](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.211.1:1995 (R2013) Paints and related materials - Methods of test - Method 211.1: Degree of settling

- [AS/NZS 1580.211.2:1995](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.211.2:1995 (R2013) Paints and related materials - Methods of test - Method 211.2: Ease of manual re-incorporation

- [AS/NZS 1580.213.1:1997 \(R2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.213.1:1997 (R2013) Paints and related materials - Methods of test - Method 213.1: Relative dry hiding power

- [AS/NZS 1580.214.0:1996 \(R2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.214.0:1996 (R2013) Paints and related materials - Methods of test - Method 214.0: Rheological properties - Guide to test methods

- [AS/NZS 1580.457.1:1996](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.457.1:1996 (R2013) Methods of test for paints and related materials -

Resistance to natural weathering

- [AS/NZS 1580.481.1.10:1998 \(Reconfirmed in 2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.481.1.10:1998 (R2013) Methods of test for paints and related materials - Exposed to weathering - Degree of flaking and peeling

- [AS/NZS 1580.481.1.11:1998 \(Reconfirmed in 2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.481.1.11:1998 (R2013) Methods of test for paints and related materials - Exposed to weathering - Degree of chalking

- [AS/NZS 1580.481.1.12:1998 \(R2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.481.1.12:1998 (R2013) Paints and related materials - Methods of test Coatings - Method 481.1.12: Exposed to weathering - Degree of colour change

- [AS/NZS 1580.481.1.2:1998 \(R2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.481.1.2:1998 (R2013) Paints and related materials - Methods of test Coatings - Method 481.1.2: Exposed to weathering - Discolouration (including bronzing)

- [AS/NZS 1580.481.1.7:1998 \(Reconfirmed in 2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.481.1.7:1998 (R2013) Methods of test for paints and related materials - Exposed to weathering - Degree of checking

- [AS/NZS 1580.481.1.8:1998 \(Reconfirmed in 2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.481.1.8:1998 (R2013) Methods of test for paints and related materials - Exposed to weathering - Degree of cracking

- [AS/NZS 1580.481.1.9:1998 \(Reconfirmed in 2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.481.1.9:1998 (R2013) Methods of test for paints and related materials - Exposed to weathering - Degree of blistering

- [AS/NZS 1580.601.1:1995](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.601.1:1995 (R2013) Methods of test for paints and related materials - Colour - Visual comparison

- [AS/NZS 1580.602.2:1995 \(R2013\)](#)

AS 3730.7-2006 (R2016) cites AS/NZS 1580.602.2:1995 (R2013) Paints and related materials - Methods of test - - Measurement of specular gloss of non-metallic paint films at 20 degrees, 60 degrees and 85 degrees

- [AS/NZS 2310:2002](#)

AS 3730.7-2006 (R2016) cites AS/NZS 2310:2002 (R2016) Glossary of paint and painting terms

Australian Standards

- [AS 1580.213.2-2004](#)

AS 3730.7-2006 (R2016) cites AS 1580.213.2-2004 Paints and related materials - Methods of test - Method 213.2: Dry hiding power - Contrast ratio

- [AS 1580.301.2-1990](#)

AS 3730.7-2006 (R2016) cites AS 1580.301.2-1990 (R2013) Paints and related materials - Methods of test - Method 301.2: Non-volatile content by volume (volume solids)

- [AS 1580.401.6-2002 \(R2013\)](#)

AS 3730.7-2006 (R2016) cites AS 1580.401.6-2002 (R2013) Paints and related materials - Methods of test - Hard dry condition (mechanical thumb test)

- [AS 1580.409.1-2002 \(R2013\)](#)

AS 3730.7-2006 (R2016) cites AS 1580.409.1-2002 (R2013) Paints and related materials - Methods of test - Resistance to mudcracking

- [AS 1580.409.2-2002 \(R2013\)](#)

AS 3730.7-2006 (R2016) cites AS 1580.409.2-2002 (R2013) Paints and related materials - Methods of test - Low temperature coalescence

- [AS 1580.603.1-2002](#)

AS 3730.7-2006 (R2016) cites AS 1580.603.1-2002 (R2013) Paints and related materials - Methods of test - Method 603.1: Finish - General appearance

- [AS 2700-1996](#)

AS 3730.7-2006 (R2016) cites AS 2700-1996 Colour Standards for general purposes

- [AS 3730.0-2006 \(R2016\)](#)

AS 3730.7-2006 (R2016) cites AS 3730.0-2006 (R2016) Guide to the properties of paints for buildings - Part 0: General information on the specification, purchasing and testing of paints

Other

- [The Poisons Standard \(the SUSMP\)](#)

AS 3730.7-2006 (R2016) cites The Poisons Standard (Standard for the Uniform Scheduling of Medicines and Poisons - SUSMP)

Table of Contents

[Save](#)

[Feedback](#)

<input type="text"/>		
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

[Feedback](#)