

Menu

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print

[Save](#)

Email

[Resource detail](#)
[Citations](#)

AS 4176.8-2010 Multilayer pipes for pressure applications - Part 8: Multilayer pipe systems for consumer gas installations with a maximum operating pressure up to and including 5 bar (500 kPa) - Specifications for systems (ISO 17484-1:2006, MOD)

[View on Information Provider website](#)

{{ linkText }}

Abbreviation
 AS 4176.8-2010
 Valid from
 30/03/2010
 Replaces
 ,

Information provider
 SAI Global
 Author
 Standards Australia
 Information type
 Australian Standard
 Format
 PDF

Cited By
[This resource is cited by 3 documents \(show Citations\)](#)

Description

This Australian Standard adopts ISO 17484-1:2006 to specify general requirements and performance requirements for pipes and joints made of multilayer construction intended to be used for consumer gas installations with a maximum operating pressure up to and including 5 bar (500 kPa).

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

{{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 4176.8-2010 Multilayer pipes for pressure applications - Part 8: Multilayer

pipe systems for consumer gas installations with a maximum operating pressure up to and including 5 bar (500 kPa) - Specifications for systems (ISO 17484-1:2006, MOD)

This document is CITED BY:

- [AS/NZS 3500.1:2015](#)

AS 4176.8-2010 is cited by AS/NZS 3500.1:2015 Plumbing and drainage - Part 1: Water services

- [AS/NZS 3500.1:2018](#)

AS 4176.8-2010 is cited by AS/NZS 3500.1:2018 Plumbing and drainage Part 1: Water services

- [AS/NZS 5601.1:2013](#)

AS 4176.8-2010 is cited by AS/NZS 5601.1:2013 Gas installations - General installations

Back

AS 4176.8-2010 Multilayer pipes for pressure applications - Part 8: Multilayer pipe systems for consumer gas installations with a maximum operating pressure up to and including 5 bar (500 kPa) - Specifications for systems (ISO 17484-1:2006, MOD)

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Australian Standard adopts ISO 17484-1:2006 to specify general requirements and performance requirements for pipes and joints made of multilayer construction intended to be used for consumer gas installations with a maximum operating pressure up to and including 5 bar (500 kPa).

[View on Information Provider website](#)

[AS 4176.8-2010 Multilayer pipes for pressure applications - Part 8: Multilayer pipe systems for consumer gas installations with a maximum operating pressure up to and including 5 bar \(500 kPa\) - Specifications for systems \(ISO 17484-1:2006, MOD\)](#)

Description

This Australian Standard adopts ISO 17484-1:2006 to specify general requirements and performance requirements for pipes and joints made of multilayer construction intended to be used for consumer gas installations with a maximum operating pressure up to and including 5 bar (500 kPa).

[View on Information Provider website](#)

This resource does not cite any other resources.

AS 4176.8-2010 Multilayer pipes for pressure applications - Part 8: Multilayer pipe systems for consumer gas installations with a maximum operating pressure up to and including 5 bar (500 kPa) - Specifications for systems (ISO 17484-1:2006, MOD)

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)