

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Resource detail](#)
[Citations](#)

AS 60269.1-2005 Low-voltage fuses - Part 1: General requirements

[View on Information Provider website](#)

Abbreviation

AS 60269.1-2005

Valid from

01/02/2005

Information provider

SAI Global

Author

Standards Australia

Information type

Australian Standard

Format

PDF

Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

Description

This Standard applies to fuses incorporating enclosed current limiting fuse links with rated breaking capacities of not less than 6 kA, intended for protecting power frequency a.c. circuits of nominal voltages not exceeding 1000 V or d.c. circuits of nominal voltages not exceeding 1500 V.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS 60269.1-2005 Low-voltage fuses - Part 1: General requirements

This document is CITED BY:

- [AS 2293.1-2005](#)

AS 60269.1-2005 is cited by AS 2293.1-2005 Emergency escape lighting and exit signs for buildings. Part 1: System design, installation and operation

- [AS/NZS 3000:2007](#)

AS 60269.1-2005 is cited by AS/NZS 3000:2007 Electrical installations (known as the Australian/New Zealand Wiring Rules)

Back

AS 60269.1-2005 Low-voltage fuses - Part 1: General requirements

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard applies to fuses incorporating enclosed current limiting fuse links with rated breaking capacities of not less than 6 kA, intended for protecting power frequency a.c. circuits of nominal voltages not exceeding 1000 V or d.c. circuits of nominal voltages not exceeding 1500 V.

[View on Information Provider website](#)

[AS 60269.1-2005 Low-voltage fuses - Part 1: General requirements](#)

Description

This Standard applies to fuses incorporating enclosed current limiting fuse links with rated breaking capacities of not less than 6 kA, intended for protecting power frequency a.c. circuits of nominal voltages not exceeding 1000 V or d.c. circuits of nominal voltages not exceeding 1500 V.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS 60269.1-2005 Low-voltage fuses - Part 1: General requirements

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

<input type="text"/>		
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

[Feedback](#)