

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

AS H8-1968 Leaded brass 58 per cent copper, 3 per cent lead rods and sections (other than forging stock)

[View on Information Provider website](#)

Abbreviation
AS H8-1968
Valid from
01/01/1968

Information provider
SAI Global
Author
Standards Australia
Information type
Australian Standard
Format
PDF, Hard copy

Cited By
[This resource is cited by 1 document \(show Citations\)](#)

Description

This standard specifies requirements for leaded brass, 58 per cent copper, 3 per cent lead (designated CZ121), rods and sections for machining and general purposes other than forging having a diameter or width across flats not less than 1/16 in (1.6 mm).

For assistance with locating previous versions, please contact the information provider.

Notes/comments

Due to the age of this archived document, available information is limited therefore this record is incomplete. For further details, please phone our Customer Service Centre on 131 242 (Intl +61 2 8206 6010) or email sales@saiglobal.com.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

Due to the age of this archived document, available information is limited therefore this record is incomplete. For further details, please phone our Customer Service Centre on 131 242 (Intl +61 2 8206 6010) or email sales@saiglobal.com.

This resource is cited by:

AS H8-1968 Leaded brass 58 per cent copper, 3 per cent lead rods and sections (other than forging stock)

This document is CITED BY:

- [AS D26: 1972](#)

AS H8-1968 is cited by AS D26-1972 (R2018) Tube fittings with dryseal American standard taper pipe and unified threads for automotive and industrial use

Back

AS H8-1968 Leaded brass 58 per cent copper, 3 per cent lead rods and sections (other than forging stock)

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This standard specifies requirements for leaded brass, 58 per cent copper, 3 per cent lead (designated CZ121), rods and sections for machining and general purposes other than forging having a diameter or width across flats not less than 1/16 in (1.6 mm).

[View on Information Provider website](#)

[AS H8-1968 Leaded brass 58 per cent copper, 3 per cent lead rods and sections \(other than forging stock\)](#)

Description

This standard specifies requirements for leaded brass, 58 per cent copper, 3 per cent lead (designated CZ121), rods and sections for machining and general purposes other than forging having a diameter or width across flats not less than 1/16 in (1.6 mm).

[View on Information Provider website](#)

This resource does not cite any other resources.

AS H8-1968 Leaded brass 58 per cent copper, 3 per cent lead rods and sections (other than forging stock)

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)

- [Copyright](#)

--	--	--

--

[Feedback](#)