

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  

[Save](#)

[Resource detail](#)

[Citations](#)

## AS ISO 6993.1-2007 (R2017) Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels - Part 1: Pipes for a maximum operating pressure of 1 bar (100 kPa) (ISO 6993-1:2006, MOD)

[View on Information Provider website](#)

### Abbreviation

AS ISO 6993.1-2007

### Valid from

12/07/2007

---

### Information provider

SAI Global

### Author

Standards Australia

### Information type

Australian Standard

### Format

PDF

---

### Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

---

### Description

This Standard adopts ISO 6993-1:2006, with modification, to specify the requirements for pipes made of high-impact poly(vinyl chloride) (PVC-HI) intended to be used for the supply of gaseous fuels through buried pipelines having an operating temperature range of 0° Celsius up to and including +30° Celsius and a maximum operating pressure of 1 bar (100 kPa).

For assistance with locating previous versions, please contact the information provider.

### Notes/comments

Standard reconfirmed on 27 April 2017

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

Standard reconfirmed on 27 April 2017

This resource is cited by:

# AS ISO 6993.1-2007 (R2017) Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels - Part 1: Pipes for a maximum operating pressure of 1 bar (100 kPa) (ISO 6993-1:2006, MOD)

This document is CITED BY:

- [AS/NZS 5601.1:2010](#)

AS ISO 6993.1-2007 is cited by AS/NZS 5601.1:2010 Gas installations - Part 1: General installations

- [AS/NZS 5601.1:2013](#)

AS ISO 6993.1-2007 is cited by AS/NZS 5601.1:2013 Gas installations - General installations

Back

# AS ISO 6993.1-2007 (R2017) Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels - Part 1: Pipes for a maximum operating pressure of 1 bar (100 kPa) (ISO 6993-1:2006, MOD)

Show what documents this resource is CITED BY

Show what documents this resource CITES

## Description

This Standard adopts ISO 6993-1:2006, with modification, to specify the requirements for pipes made of high-impact poly(vinyl chloride) (PVC-HI) intended to be used for the supply of gaseous fuels through buried pipelines having an operating temperature range of 0° Celsius up to and including +30° Celsius and a maximum operating pressure of 1 bar (100 kPa).

[View on Information Provider website](#)

[AS ISO 6993.1-2007 \(R2017\) Buried, high-impact poly\(vinyl chloride\) \(PVC-HI\) piping systems for the supply of gaseous fuels - Part 1: Pipes for a maximum operating pressure of 1 bar \(100 kPa\) \(ISO 6993-1:2006, MOD\)](#)

## Description

This Standard adopts ISO 6993-1:2006, with modification, to specify the requirements for pipes made of high-impact poly(vinyl chloride) (PVC-HI) intended to be used for the supply of gaseous fuels through buried pipelines having an operating temperature range of 0° Celsius up to and including +30° Celsius and a maximum operating pressure of 1 bar (100 kPa).

[View on Information Provider website](#)

This resource does not cite any other resources.

# AS ISO 6993.1-2007 (R2017) Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels - Part 1: Pipes for a maximum operating pressure of 1 bar (100 kPa) (ISO 6993-1:2006, MOD)

This resource does not CITE any other resources.

Back

Close

## Table of Contents

Print [Save](#) Email

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)