

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)

[Citations](#)

AS ISO 6993.3-2007 (R2017) Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels - Part 3: Fittings and saddles for a maximum operating pressure of 1 bar (100 kPa)

[View on Information Provider website](#)

Abbreviation

AS ISO 6993.3-2007

Valid from

12/07/2007

Information provider

SAI Global

Author

Standards Australia

Information type

Australian Standard

Format

PDF

Cited By

[This resource is cited by 2 documents \(show Citations\)](#)

Description

This Standard adopts ISO 6993-3:2006, which specifies the requirements for full-end load-bearing fittings made of high-impact poly(vinyl chloride) (PVC-HI) intended to be used for the supply of gaseous fuels through buried pipelines having an operating temperature range of 0° Celsius up to and including +30° Celsius and a maximum operating pressure of 1 mbar (100 kPa).

For assistance with locating previous versions, please contact the information provider.

Notes/comments

Standard reconfirmed on 2007-07-12

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

Standard reconfirmed on 2007-07-12

This resource is cited by:

AS ISO 6993.3-2007 (R2017) Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels - Part 3: Fittings and saddles for a maximum operating pressure of 1 bar (100 kPa)

This document is CITED BY:

- [AS/NZS 5601.1:2010](#)

AS ISO 6993.3-2007 is cited by AS/NZS 5601.1:2010 Gas installations - Part 1: General installations

- [AS/NZS 5601.1:2013](#)

AS ISO 6993.3-2007 is cited by AS/NZS 5601.1:2013 Gas installations - General installations

Back

AS ISO 6993.3-2007 (R2017) Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels - Part 3: Fittings and saddles for a maximum operating pressure of 1 bar (100 kPa)

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Standard adopts ISO 6993-3:2006, which specifies the requirements for full-end load-bearing fittings made of high-impact poly(vinyl chloride) (PVC-HI) intended to be used for the supply of gaseous fuels through buried pipelines having an operating temperature range of 0° Celsius up to and including +30° Celsius and a maximum operating pressure of 1 mbar (100 kPa).

[View on Information Provider website](#)

[AS ISO 6993.3-2007 \(R2017\) Buried, high-impact poly\(vinyl chloride\) \(PVC-HI\) piping systems for the supply of gaseous fuels - Part 3: Fittings and saddles for a maximum operating pressure of 1 bar \(100 kPa\)](#)

Description

This Standard adopts ISO 6993-3:2006, which specifies the requirements for full-end load-bearing fittings made of high-impact poly(vinyl chloride) (PVC-HI) intended to be used for the supply of gaseous fuels through buried pipelines having an operating temperature range of 0° Celsius up to and including +30° Celsius and a maximum operating pressure of 1 mbar (100 kPa).

[View on Information Provider website](#)

This resource does not cite any other resources.

AS ISO 6993.3-2007 (R2017) Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels - Part 3: Fittings and saddles for a maximum operating pressure of 1 bar (100 kPa)

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print [Save](#) Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)