Skip to main content Skip to primary navigation  Menu  Menu
<ul> <li>Home Home</li> <li>About this portal</li> <li>Latest updates</li> </ul>
Print Save Email Resource detail

# ASME B36.19M:2004 (R2015) Stainless Steel Pipe

<u>View on Information Provider website</u> {{ linkText }}

Abbreviation ASME B36.19M:2004 Valid from 25/10/2004

Information provider IHS Markit

Author

Citations

American Society of Mechanical Engineers

Information type

Other Standard

**Format** 

PDF, Hard copy

Cited By

This resource is cited by 3 documents (show Citations)

### Description

This Standard covers the standardization of dimensions of welded and seamless wrought stainless steel pipe for high or low temperatures and pressures.

The word pipe is used, as distinguished from tube, to apply to tubular products of dimensions commonly used for pipeline and piping systems. Pipes NPS 12 (DN 300) and smaller have outside diameters numerically larger than their corresponding sizes. In contrast, the outside diameters of tubes are numerically identical to the size number for all sizes.

The wall thicknesses for NPS 14 through 22, inclusive (DN 350–550, inclusive), of Schedule 10S; NPS 12 (DN 300) of Schedule 40S; and NPS 10 and 12 (DN 250 and 300) of Schedule 80S are not the same as those of ASME B36.10M. The suffix "S" in the schedule number is used to differentiate B36.19M pipe from B36.10M pipe. ASME B36.10M includes other pipe thicknesses that are also commercially available with stainless steel material.

For assistance with locating previous versions, please contact the information provider.

<u>View on Information Provider website</u> {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

# ASME B36.19M:2004 (R2015) Stainless Steel Pipe

This document is CITED BY:

AS 3688:2005

ASME B36.19M:2004 is cited by AS 3688:2005 Water supply - Metallic fittings and end connectors

• AS/NZS 3500.1:2018

ASME B36.19M:2004 is cited by AS/NZS 3500.1:2018 Plumbing and drainage Part 1: Water services

AS/NZS 5601.1:2013

ASME B36.19M:2004 is cited by AS/NZS 5601.1:2013 Gas installations - General installations

Back

# ASME B36.19M:2004 (R2015) Stainless Steel Pipe

Show what documents this resource is CITED BY

Show what documents this resource CITES

#### Description

This Standard covers the standardization of dimensions of welded and seamless wrought stainless steel pipe for high or low temperatures and pressures.

The word pipe is used, as distinguished from tube, to apply to tubular products of dimensions commonly used for pipeline and piping systems. Pipes NPS 12 (DN 300) and smaller have outside diameters numerically larger than their corresponding sizes. In contrast, the outside diameters of tubes are numerically identical to the size number for all sizes.

The wall thicknesses for NPS 14 through 22, inclusive (DN 350–550, inclusive), of Schedule 10S; NPS 12 (DN 300) of Schedule 40S; and NPS 10 and 12 (DN 250 and 300) of Schedule 80S are not the same as those of ASME B36.10M. The suffix "S" in the schedule number is used to differentiate B36.19M pipe from B36.10M pipe. ASME B36.10M includes other pipe thicknesses that are also commercially available with stainless steel material.

View on Information Provider website

ASME B36.19M:2004 (R2015) Stainless Steel Pipe

### Description

This Standard covers the standardization of dimensions of welded and seamless wrought stainless steel pipe for high or low temperatures and pressures.

The word pipe is used, as distinguished from tube, to apply to tubular products of dimensions commonly used for pipeline and piping systems. Pipes NPS 12 (DN 300) and smaller have outside diameters numerically larger than their corresponding sizes. In contrast, the outside diameters of tubes are numerically identical to the size number for all sizes.

The wall thicknesses for NPS 14 through 22, inclusive (DN 350–550, inclusive), of Schedule 10S; NPS 12 (DN 300) of Schedule 40S; and NPS 10 and 12 (DN 250 and 300) of Schedule 80S are not the same as those of ASME B36.10M. The suffix "S" in the schedule number is used to differentiate B36.19M pipe from B36.10M pipe. ASME B36.10M includes other pipe thicknesses that are also commercially available with stainless steel material.

View on Information Provider website

This resource does not cite any other resources.

# ASME B36.19M:2004 (R2015) Stainless Steel Pipe

This resource does not CITE any other resources.

Back
Close

### **Table of Contents**

Print Save Email		
<u>Feedback</u>		
• Contact us		
<ul> <li>Privacy policy</li> </ul>		
• <u>Disclaimer</u>		
<ul> <li>Copyright</li> </ul>		

<u>Feedback</u>