

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

AS/NZS 1050.27:1994 (R016) Methods for the analysis of iron and steel - Part 27: Determination of titanium content - Spectrophotometric method

[View on Information Provider website](#)

Abbreviation

AS/NZS 1050.27:1994

Valid from

18/09/1994

Information provider

Standards New Zealand

Author

Standards New Zealand, Standards Australia

Information type

New Zealand Standard

Format

PDF

Cited By

[This resource is cited by 3 documents \(show Citations\)](#)

Description

This Method specifies a spectrophotometric method using diantipyryl-methane as a chromogen, measured spectrophotometrically at 390 nm. The method can be used for the determination of titanium content between 0.005 percent and 1.20 percent in steel.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS/NZS 1050.27:1994 (R016) Methods for the analysis of iron and steel - Part 27: Determination of titanium content - Spectrophotometric method

This document is CITED BY:

- [AS 1397-2011](#)

AS/NZS 1050.27:1994 is cited by AS 1397-2011 Continuous hot-dip metallic coated steel sheet and strip - Coatings of zinc and zinc alloyed with aluminium and magnesium

- [AS 1397:2001](#)

AS/NZS 1050.27:1994 is cited by AS 1397:2001 Steel sheet and strip - Hot-dipped zinc-coated or aluminium/zinc-coated

- [AS/NZS 4671:2001](#)

AS/NZS 1050.27:1994 is cited by AS/NZS 4671:2001 Steel reinforcing materials

Back

AS/NZS 1050.27:1994 (R016) Methods for the analysis of iron and steel - Part 27: Determination of titanium content - Spectrophotometric method

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This Method specifies a spectrophotometric method using diantipyryl-methane as a chromogen, measured spectrophotometrically at 390 nm. The method can be used for the determination of titanium content between 0.005 percent and 1.20 percent in steel.

[View on Information Provider website](#)

[AS/NZS 1050.27:1994 \(R016\) Methods for the analysis of iron and steel - Part 27: Determination of titanium content - Spectrophotometric method](#)

Description

This Method specifies a spectrophotometric method using diantipyryl-methane as a chromogen, measured spectrophotometrically at 390 nm. The method can be used for the determination of titanium content between 0.005 percent and 1.20 percent in steel.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS/NZS 1050.27:1994 (R016) Methods for the analysis of iron and steel - Part 27: Determination of titanium content - Spectrophotometric method

This resource does not CITE any other resources.

Back

Close

Table of Contents

1 Scope

2 Referenced Documents

3 Principle

4 Reagents

5 Apparatus

6 Sampling

7 Procedure

8 Procedure

9 Calculations

10 Precision

11 Acceptance Of Analytical Values

12 Test Report

[Save](#)

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)