| Skip to main content Skip to  | o primary navigation |   |
|---|----------------------|---|
| <ul> <li><u>Home Home</u></li> <li><u>About this portal</u></li> <li><u>Latest updates</u></li> </ul> |                      |   |
| Print Save Email  |                      | ] |
| Resource detail<br>Citations  |                      |   |

## AS/NZS 1125:2001 Conductors in insulated electric cables and flexible cords

| Table of Contents  |
|--|
| View on Information Provider website {{ linkText }}  |
| Abbreviation<br>AS/NZS 1125:2001<br>Amendment<br>AS/NZS 1125:2001 A1 incorporated. Published 22/08/2004.<br>Valid from<br>28/06/2001 |
| Information provider<br>Standards New Zealand<br>Author  |

Standards New Zealand, Standards Australia Information type New Zealand Standard Format PDF

Cited By <u>This resource is cited by 2 documents (show Citations)</u>

#### Description

This Standard specifies the requirements for conductors in insulated electric cables and flexible cords used for general wiring cables for land installations and, in the case of copper conductors only, for ships' wiring.

The Standard does not apply to material used for the manufacture of conductors.

#### Scope

This Standard applies particularly to conductors for those types of cable and flexible cord to which the relevant Australian or Australian/New Zealand Standard makes cross-reference. This Standard is not necessarily limited to conductors of such cables and cords and should be applied, wherever practicable, to cables designed for general and special purposes.

The conductors specified here do not apply to the following:

- (a) Magnet winding wire including litz wire (see AS/NZS 1194.1).
- (b) Mineral-insulated metal-sheathed (MIMS) cables (see AS/NZS 3187).
- (c) Cables intended for use at audio or higher frequencies, e.g. telecommunication cables.
- (d) Welding cables (see AS/NZS 1995)

For assistance with locating previous versions, please contact the information provider.

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

#### AS/NZS 1125:2001 Conductors in insulated electric cables and flexible cords

This document is CITED BY:

• <u>AS/NZS 5000.1:2005</u>

AS/NZS 1125:2001 is cited by AS/NZS 5000.1:2005 Electric cables - Polymeric insulated - For working voltages up to and including 0.6/1 (1.2) kV

• <u>AS/NZS 5000.2:2006</u>

AS/NZS 1125:2001 is cited by AS/NZS 5000.2:2006 Electric cables - Polymeric insulated - For working voltages up to and including 450/750 V

Back

## AS/NZS 1125:2001 Conductors in insulated electric cables and flexible cords

Show what documents this resource is CITED BY Show what documents this resource CITES

Description

This Standard specifies the requirements for conductors in insulated electric cables and flexible cords used for general wiring cables for land installations and, in the case of copper conductors only, for ships' wiring.

The Standard does not apply to material used for the manufacture of conductors.

View on Information Provider website

AS/NZS 1125:2001 Conductors in insulated electric cables and flexible cords

#### Description

This Standard specifies the requirements for conductors in insulated electric cables and flexible cords used for general wiring cables for land installations and, in the case of copper conductors only, for ships' wiring.

The Standard does not apply to material used for the manufacture of conductors.

View on Information Provider website

This resource does not cite any other resources.

#### AS/NZS 1125:2001 Conductors in insulated electric cables and flexible cords

This resource does not CITE any other resources.

| Back  |  |
|-------|--|
| Close |  |

Table of Contents

## 1 Scope And General

#### 1.1 Scope

**1.2 Referenced Documents** 

#### **1.3 Definitions**

- 1.3.1 Bunched Circular Conductor
- 1.3.2 Circular Conductor
- 1.3.3 Compacted Conductor
- 1.3.4 Compressed Conductor
- 1.3.5 Conductor
- 1.3.6 Metal-Coated Copper Conductor
- 1.3.7 Milliken Conductor
- 1.3.8 Multiple Stranded Circular Conductor (Rope Lay)
- 1.3.9 Routine Tests
- 1.3.10 Sample Tests
- 1.3.11 Shaped Conductor
- 1.3.12 Solid Conductor
- 1.3.13 Solid Sectoral Circular Conductor
- 1.3.14 Stranded Conductor
- 1.3.15 Tinsel Conductor
- 1.3.16 Uniaxial Conductor
- 1.4 Conductor Maximum D.C Resistance
- **2 Copper Conductors**
- 2.1 General
- 2.2 Material
- 2.3 Form Of Conductor
- 2.4 Joints In Conductors
- 2.4.1 Joints In Annealed Conductors
- 2.4.2 Joints In Hard drawn Conductors
- 2.5 Solid Conductors (Class 1)

- 2.6 Stranded Conductors (Class 2)
- 2.7 Uniaxial Conductors
- 2.8 Flexible Conductors (Class 5)
- 2.9 Flexible Conductors (Class 6)
- 2.10 Multiple Stranded Circular Flexible Conductors (Rope Lay)
- 2.11 Tinsel Conductors
- **3 Aluminium Conductors**
- 3.1 General
- 3.2 Material
- 3.2.1 Alloy
- 3.2.2 Stranded Conductors
- 3.2.3 Solid Conductors
- 3.3 For Of Conductor
- 3.4 Joints In Conductors
- 3.4 1 Stranded Conductors Other Than In Aerial Cables
- 3.4.2 Stranded Conductors In Aerial Cables
- 3.4.3 Solid Conductors
- 3.5 Solid Conductors (Class 1)
- 3.6 Stranded Conductors (Class 2)
- Appendix A Method Of Calculation Of Conductor Maximum Resistance
- A1 General

# A2 Method Of Calculation Of Conductor Maximum



- <u>Contact us</u>
- Privacy policy
- Disclaimer

<u>Copyright</u>

|          |  | - |
|----------|--|---|
| Feedback |  |   |