Skip to main content Skip to primary navigation	
Menu	
 <u>Home</u> <u>About this portal</u> <u>Latest updates</u> 	
Print Save Email Resource detail Citations	

AS/NZS 1301.421s:1998 Methods of test for pulp and paper -Method 421s: Determination of the pH value of aqueous extracts of paper, board and pulp - Cold extraction method

Table of Contents

View on Information Provider website {{ linkText }}

Abbreviation AS/NZS 1301.421s:1998 Valid from 04/06/1998

Information provider Standards New Zealand Author Standards New Zealand, Standards Australia Information type New Zealand Standard Format Hard copy, PDF

Cited By <u>This resource is cited by 1 document (show Citations)</u>

Description

This method applies to an extract of the whole paper or board. Surface-treated papers or boards may yield quite different pH for an extract of the surface layer from that of the whole paper or board.

The determination of the pH value of distilled water extracts of paper is a test commonly used by paper manufacturers and paper users, when a knowledge of the degree of acidity or alkalinity of the paper is considered desirable for assessing whether the paper will be satisfactory for a particular purpose. Papers requiring a high degree of permanence, or intended for hygienic purposes, or for the wrapping of foods and metals are examples of papers that may be subjected to this test.

This standard prescribes a cold water extraction of paper. AS/NZS 1301.422s prescribes hot extraction, but, as this does not necessarily give the same results, it should be regarded as a different method. The difference is due to heat-induced hydrolysis of materials in the paper. The choice of method is determined by the use to which the results are to be put, and the references listed in annex A should be consulted.

This method conforms to the relevant cold extraction sections of ISO 6588:1981, *Paper, board and pulps – Determination of pH of aqueous extracts*.

For assistance with locating previous versions, please contact the information provider.

 Table of Contents
 View on Information Provider website
 {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS/NZS 1301.421s:1998 Methods of test for pulp and paper -Method 421s: Determination of the pH value of aqueous extracts of paper, board and pulp - Cold extraction method

This document is CITED BY:

• NZS 2295: 2006

AS/NZS 1301.421s:1998 is cited by NZS 2295: 2006 Pliable, permeable building underlays

Back

AS/NZS 1301.421s:1998 Methods of test for pulp and paper -Method 421s: Determination of the pH value of aqueous extracts of paper, board and pulp - Cold extraction method

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This method applies to an extract of the whole paper or board. Surface-treated papers or boards may yield quite different pH for an extract of the surface layer from that of the whole paper or board.

The determination of the pH value of distilled water extracts of paper is a test commonly used by paper manufacturers and paper users, when a knowledge of the degree of acidity or alkalinity of the paper is considered desirable for assessing whether the paper will be satisfactory for a particular purpose. Papers requiring a high degree of permanence, or intended for hygienic purposes, or for the wrapping of foods and metals are examples of papers that may be subjected to this test.

This standard prescribes a cold water extraction of paper. AS/NZS 1301.422s prescribes hot extraction, but, as this does not necessarily give the same results, it should be regarded as a different method. The difference is due to heat-induced hydrolysis of materials in the paper. The choice of method is determined by the use to which the results are to be put, and the references listed in annex A should be consulted.

This method conforms to the relevant cold extraction sections of ISO 6588:1981, *Paper, board and pulps – Determination of pH of aqueous extracts*.

View on Information Provider website

AS/NZS 1301.421s:1998 Methods of test for pulp and paper - Method 421s: Determination of the pH value of aqueous extracts of paper, board and pulp - Cold extraction method

Description

This method applies to an extract of the whole paper or board. Surface-treated papers or boards may yield quite different pH for an extract of the surface layer from that of the whole paper or board.

The determination of the pH value of distilled water extracts of paper is a test commonly used by paper manufacturers and paper users, when a knowledge of the degree of acidity or alkalinity of the paper is considered desirable for assessing whether the paper will be satisfactory for a particular purpose. Papers requiring a high degree of permanence, or intended for hygienic purposes, or for the wrapping of foods and metals are examples of papers that may be subjected to this test.

This standard prescribes a cold water extraction of paper. AS/NZS 1301.422s prescribes hot extraction, but, as this does not necessarily give the same results, it should be regarded as a different method. The difference is due to heat-induced hydrolysis of materials in the paper. The choice of method is determined by the use to which the results are to be put, and the references listed in annex A should be consulted.

This method conforms to the relevant cold extraction sections of ISO 6588:1981, *Paper, board and pulps – Determination of pH of aqueous extracts*.

View on Information Provider website

This resource does not cite any other resources.

AS/NZS 1301.421s:1998 Methods of test for pulp and paper - Method 421s: Determination of the pH value of aqueous

extracts of paper, board and pulp - Cold extraction method

This resource does not CITE any other resources.

Back	
Close	1

Table of Contents

- 1 Scope
- **2 Normative References**
- **3 Principle**
- 4 Apparatus
- 4.1 Glassware Of Chemically Resistant Glass
- 4.2 Ph Meter
- **5 Reagents**
- 5.1 Distilled Or Deionized Water
- 5.2 Ph Standards
- Ph 4.00 At 20 Degrees C
- Ph 6.87 At 20 Degrees C
- Ph 9.23 At 20 Degrees C
- **6 Preparation Of Sample**
- 7 Procedure
- **8 Expression Of Results**

9 Report

Annex A

Bibliography

Print <u>Save</u> Email		
eedback		
Oraclast		
<u>Contact us</u>		
 Privacy policy 		

- <u>Disclaimer</u>
- <u>Copyright</u>



Feedback