

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Resource detail](#)
[Citations](#)

AS/NZS 1580.205.4:1998 (R2013) Paints and related materials - Methods of test - Method 205.4: Application properties - Airless spraying

[View on Information Provider website](#)

Abbreviation

AS/NZS 1580.205.4:1998

Valid from

04/06/1998

Information provider

Standards New Zealand

Author

Standards New Zealand, Standards Australia

Information type

New Zealand Standard

Format

PDF

Cited By

[This resource is cited by 5 documents \(show Citations\)](#)

Description

This Standard sets out a procedure for determining the suitability of a paint for application by airless spraying. It provides for the assessment of defects observed during and after application of the paint.

For assistance with locating previous versions, please contact the information provider.

Notes/comments

Standard reconfirmed 19 September 2013

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

Standard reconfirmed 19 September 2013

This resource is cited by:

AS/NZS 1580.205.4:1998 (R2013) Paints and related materials - Methods of test - Method 205.4: Application properties - Airless spraying

This document is CITED BY:

- [AS 3730.10-2006](#)

AS/NZS 1580.205.4:1998 is cited by AS 3730.10-2006 (R2016) Guide to the properties of paints for buildings. Part 10: Latex - Exterior - Gloss

- [AS 3730.6-2006 \(R2016\)](#)

AS/NZS 1580.205.4:1998 is cited by AS 3730.6-2006 (R2016) Guide to the properties of paints for buildings. Part 6: Solvent-borne - Exterior - Full gloss enamel

- [AS 3730.7-2006 \(R2016\)](#)

AS/NZS 1580.205.4:1998 is cited by AS 3730.7-2006 (R2016) Guide to the properties of paints for buildings. Part 7: Latex - Exterior - Flat

- [AS 3730.8-2006 \(R2016\)](#)

AS/NZS 1580.205.4:1998 is cited by AS 3730.8-2006 (R2016) Guide to the properties of paints for buildings. Part 8: Latex - Exterior - Low-gloss

- [AS 3730.9-2006 \(R2016\)](#)

AS/NZS 1580.205.4:1998 is cited by AS 3730.9-2006 (R2016) Guide to the properties of paints for buildings. Part 9: Latex - Exterior - Semi-gloss

[Back](#)

AS/NZS 1580.205.4:1998 (R2013) Paints and related materials - Methods of test - Method 205.4: Application properties - Airless spraying

[Show what documents this resource is CITED BY](#)

[Show what documents this resource CITES](#)

Description

This Standard sets out a procedure for determining the suitability of a paint for application by airless spraying. It provides for the assessment of defects observed during and after application of the paint.

[View on Information Provider website](#)

[AS/NZS 1580.205.4:1998 \(R2013\) Paints and related materials - Methods of test - Method 205.4: Application properties - Airless spraying](#)

Description

This Standard sets out a procedure for determining the suitability of a paint for application by airless spraying. It provides for the assessment of defects observed during and after application of the paint.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS/NZS 1580.205.4:1998 (R2013) Paints and related materials - Methods of test - Method 205.4: Application properties - Airless spraying

This resource does not CITE any other resources.

Back

Close

Table of Contents

1 Scope

2 Referenced Documents

3 Definition

3.1 Airless Spraying

4 Principle

5 Apparatus

6 Test Panel

7 Sample

8 Test Conditions

9 Procedure

10 Report

Print

[Save](#)

Email

[Feedback](#)

| | | |
|----------------------|----------------------|----------------------|
| <input type="text"/> | | |
| <input type="text"/> | <input type="text"/> | <input type="text"/> |
| <input type="text"/> | | |

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

| | | |
|----------------------|----------------------|----------------------|
| <input type="text"/> | <input type="text"/> | <input type="text"/> |
| <input type="text"/> | | |

[Feedback](#)