

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  
 

[Save](#)

[Resource detail](#)  
[Citations](#)

## AS/NZS 2280:1995 Ductile iron pressure pipes and fittings

[View on Information Provider website](#)

### Abbreviation

AS/NZS 2280:1995

### Valid from

05/04/1995

---

### Information provider

Standards New Zealand

### Author

Standards New Zealand, Standards Australia

### Information type

New Zealand Standard

### Format

PDF

---

### Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

### Description

This Standard specifies requirements for ductile iron pressure pipes and fittings of nominal sizes up to and including DN 750 intended for the conveyance of water under pressure. Two classes of pipes designated K9 and K12 are specified on the basis of wall thickness and are consistent with ISO 2531.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## AS/NZS 2280:1995 Ductile iron pressure pipes and fittings

This document is CITED BY:

- [AS/NZS 2566.1:1998](#)

AS/NZS 2280:1995 is cited by AS/NZS 2566.1:1998 (R2018) Buried Flexible pipelines. Structural Design

Back

## AS/NZS 2280:1995 Ductile iron pressure pipes and fittings

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

This Standard specifies requirements for ductile iron pressure pipes and fittings of nominal sizes up to and including DN 750 intended for the conveyance of water under pressure. Two classes of pipes designated K9 and K12 are specified on the basis of wall thickness and are consistent with ISO 2531.

[View on Information Provider website](#)

[AS/NZS 2280:1995 Ductile iron pressure pipes and fittings](#)

### Description

This Standard specifies requirements for ductile iron pressure pipes and fittings of nominal sizes up to and including DN 750 intended for the conveyance of water under pressure. Two classes of pipes designated K9 and K12 are specified on the basis of wall thickness and are consistent with ISO 2531.

[View on Information Provider website](#)

This resource does not cite any other resources.

## AS/NZS 2280:1995 Ductile iron pressure pipes and fittings

This resource does not CITE any other resources.

Back

Close

### Table of Contents

Print [Save](#) Email

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)