Skip to main content Skip	o to primary navigation	
Men	u	
<ul><li> Home Home</li><li> About this portal</li><li> Latest updates</li></ul>		
Print Save Email		
Resource detail		

# AS/NZS 4548.2:1999 (R2013) Guide to long-life coatings for concrete and masonry - Latex finish coatings - High-build, low profile

Table of Contents

View on Information Provider website {{ linkText }}

Abbreviation

AS/NZS 4548.2:1999

Valid from

Citations

04/04/1999

Information provider

Standards New Zealand

Author

Standards New Zealand, Standards Australia

Information type

New Zealand Standard

**Format** 

**PDF** 

Cited By

This resource is cited by 1 document (show Citations)

### Description

This Standard provides a guide to the features and typical characteristics of long-life, high-build, low profile latex type finish protective coatings intended for exterior or interior use on concrete and masonry, when applied by airless spray or roller in accordance with the manufacturers instructions.

### Scope

Paints covered by this Standard are classified as paint Type 38 of AS 2311 and correspond generally to the Australian Paint Approval Scheme specification Type 3 of GPC-C-117.

High-build, low profile latex finish coatings are water-based coatings that are designed to be used over texture coatings to elevate the exposure performance of the paint system.

These coatings provide a non-aggregate, water-resistant finish which has suitable rheological properties to produce an even film coverage over an irregular surface profile provided by the underlying texture coating. They are used to elevate the performance of the underlying coating and they also provide dirt-shedding and anti-carbonation properties.

These coatings are not intended for use on horizontal surfaces where water ponding is possible. They are normally specified in systems that may have a sealer and multiple coats.

These finish coatings are generally applied by nap roller, but can be airless spray applied, to typically achieve a spreading rate of 1.56.5 m2/L (0.670.15 L/m2). They can be used with a specified primer as stand-alone coatings to provide a low relief texture, such as a stipple finish produced with a nap roller.

For assistance with locating previous versions, please contact the information provider.

Table of Contents View on Information Provider website {{ linkText }}

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## AS/NZS 4548.2:1999 (R2013) Guide to long-life coatings for concrete and masonry - Latex finish coatings - High-build, low profile

This document is CITED BY:

NZS 3101.1&2:2006

AS/NZS 4548.2:1999 is cited by NZS 3101.1&2:2006 Concrete structures standard. The design of concrete structures



## AS/NZS 4548.2:1999 (R2013) Guide to long-life coatings for concrete and masonry - Latex finish coatings - High-build, low profile

Show what documents this resource is CITED BY

Show what documents this resource CITES

#### Description

This Standard provides a guide to the features and typical characteristics of long-life, high-build, low profile latex type finish protective coatings intended for exterior or interior use on concrete and masonry, when applied by airless spray or roller in accordance with the manufacturers instructions.

View on Information Provider website

AS/NZS 4548.2:1999 (R2013) Guide to long-life coatings for concrete and masonry - Latex finish coatings - High-build, low profile

#### Description

This Standard provides a guide to the features and typical characteristics of long-life, high-build, low profile latex type finish protective coatings intended for exterior or interior use on concrete and masonry, when applied by airless spray or roller in accordance with the manufacturers instructions.

View on Information Provider website

This resource does not cite any other resources.

## AS/NZS 4548.2:1999 (R2013) Guide to long-life coatings for concrete and masonry - Latex finish coatings - High-build, low profile

This resource does not CITE any other resources.



**Table of Contents** 

1 Scope
2 Referenced Documents
3 Definitions
3.1 System
3.2 System Integrity
3.3 Working Up
4 Typical Properties And Characteristics
4.1 Composition
4.2 Conditions Of Test
4.3 Liquid Paint
4.4 Application Properties
4.5 Applied Film
5 Packaging
6 Labelling
Appendix A - Guidance On The Use And Application Of High-Build Low Profile Latex Finish Coatings
Appendix B - List Of Referenced Documents
Print Save Email Feedback
<ul> <li>Contact us</li> <li>Privacy policy</li> <li>Disclaimer</li> <li>Copyright</li> </ul>
<u>Feedback</u>