

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

Print [Save](#) Email

[Resource detail](#)

[Citations](#)

## AS/NZS 4548.4:1999 (R2013) Guide to long-life coatings for concrete and masonry - Latex - Textured coatings - Aggregate filled

Table of Contents

[View on Information Provider website](#) `{{ linkText }}`

### Abbreviation

AS/NZS 4548.4:1999

### Valid from

04/04/1999

---

### Information provider

Standards New Zealand

### Author

Standards New Zealand, Standards Australia

### Information type

New Zealand Standard

### Format

PDF

---

### Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

### Description

This Standard provides a guide to the features and typical characteristics of long-life, aggregate-filled, textured coatings, intended for exterior or interior use on concrete and masonry, when applied by textured roller, hopper spray or trowel in accordance with the manufacturers instructions.

### Scope

Paints covered by this Standard are classified as paint Type 38 of AS 2311 and correspond generally to Australian Paint Approval Scheme specification Type 4 of GPCC- 117. Aggregate-filled, medium to high profile textured coatings are selected for aesthetic purposes and to provide maximum relief of underlying surface irregularities.

The aggregate may consist of sand, marble or other inert mineral constituent. These coatings may be applied by textured roller, hopper spray or trowel, dependent upon the material type selected and the profile required, to achieve a coverage of 0.41.2 m<sup>2</sup>/L (2.50.8 L/m<sup>2</sup>).

These coatings are generally specified in a system, including a topcoat as characterized by AS/NZS 4548.2, where maximum resistance to moisture ingress and dirt pick-up is required.

These coatings are not intended for use on horizontal surfaces where water ponding is possible. They are normally specified in systems that may have a sealer and multiple coats.

For assistance with locating previous versions, please contact the information provider.

[Table of Contents](#) [View on Information Provider website](#) [{{ linkText }}](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

## **AS/NZS 4548.4:1999 (R2013) Guide to long-life coatings for concrete and masonry - Latex - Textured coatings - Aggregate filled**

This document is CITED BY:

- [NZS 3101.1&2:2006](#)

AS/NZS 4548.4:1999 is cited by NZS 3101.1&2:2006 Concrete structures standard. The design of concrete structures

[Back](#)

## **AS/NZS 4548.4:1999 (R2013) Guide to long-life coatings for concrete and masonry - Latex - Textured coatings - Aggregate filled**

[Show what documents this resource is CITED BY](#)

[Show what documents this resource CITES](#)

### **Description**

This Standard provides a guide to the features and typical characteristics of long-life, aggregate-filled, textured coatings, intended for exterior or interior use on concrete and masonry, when applied by textured roller, hopper spray or trowel in accordance with the manufacturers instructions.

[View on Information Provider website](#)

[AS/NZS 4548.4:1999 \(R2013\) Guide to long-life coatings for concrete and masonry - Latex - Textured coatings - Aggregate filled](#)

### **Description**

This Standard provides a guide to the features and typical characteristics of long-life, aggregate-filled, textured coatings, intended for exterior or interior use on concrete and masonry, when applied by textured roller, hopper spray or trowel in accordance with the manufacturers instructions.

[View on Information Provider website](#)

This resource does not cite any other resources.

## **AS/NZS 4548.4:1999 (R2013) Guide to long-life coatings for concrete and masonry - Latex - Textured coatings - Aggregate filled**

This resource does not CITE any other resources.

[Back](#)

[Close](#)

[Table of Contents](#)

### **1 Scope**

## 2 Referenced Documents

## 3 Definitions

### 3.1 Aggregate

### 3.2 System

### 3.3 System Integrity

### 3.4 Working Up

## 4 Typical Properties And Characteristics

### 4.1 Composition

### 4.2 Conditions Of Test

### 4.3 Liquid Paint

### 4.4 Application Properties

### 4.5 Applied Film

## 5 Packaging

## 6 Labelling

## Appendix A - Guidance On The Use And Application Of Aggregate-Filled, Textured Latex Coatings

## Appendix B - List Of Referenced Documents

Print [Save](#) Email

[Feedback](#)


- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)


[Feedback](#)