

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

AS/NZS 4763(Int):2006 Safety of portable inverters

[View on Information Provider website](#)

Abbreviation

AS/NZS 4763(Int):2006

Amendment

AS/NZS 4763(Int):2006 A1 - incorporated, published 08/02/2009.

Valid from

19/10/2006

Information provider

Standards New Zealand

Author

Standards New Zealand, Standards Australia

Information type

New Zealand Standard

Format

PDF

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This Standard applies to single-phase or polyphase, air-cooled (natural or forced) portable inverters having a rated supply voltage not exceeding 60 V ripple-free d.c. and an alternating current (a.c.) output where the rated output does not exceed 3 kVA; the rated output voltage is within the range 50 500 V a.c.; and the rated frequency of the output is within the range 40 100 Hz.

It is applicable to isolated inverters, equipotentially bonded inverters and RCD protected inverters for household and similar use, use on construction sites, or providing an independent supply to electrical installations in buildings, vehicles, caravans, boats and the like. Inverters may be fitted with terminals for the connection of d.c. supply, an external flexible cord fitted with battery clips, an automobile cigarette lighter plug or other d.c. plug.

Scope

This Interim Standard applies to single-phase or polyphase, air-cooled (natural or forced) **portable inverters** having a **rated supply voltage** not exceeding 60 V ripple-free d.c. and an alternating current (a.c.) output where:

- the **rated output** does not exceed 3 kVA;
- the **rated output voltage** is within the range 50 500 V a.c.;
- the **rated frequency** of the output is within the range 40 100 Hz.

This Interim Standard is applicable to **inverters** of the following types :

- **isolated inverters**
- **equipotentially bonded inverters**
- **RCD protected inverters**

These **inverters** are for

- household and similar use,
- use on construction sites, or
- providing an independent supply to electrical installations in buildings, vehicles, caravans, boats and the like.

They may be fitted with terminals for the connection of d.c. supply or a **external flexible cord** fitted with battery clips or an automobile cigarette lighter plug or other d.c. plug.

For assistance with locating previous versions, please contact the information provider.

[Table of Contents](#) [View on Information Provider website](#) [{{ linkText }}](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

AS/NZS 4763(Int):2006 Safety of portable inverters

This document is CITED BY:

- [AS/NZS 3000:2007](#)

AS/NZS 4763(Int):2006 is cited by AS/NZS 3000:2007 Electrical installations (known as the Australian/New Zealand Wiring Rules)

[Back](#)

AS/NZS 4763(Int):2006 Safety of portable inverters

[Show what documents this resource is CITED BY](#)

[Show what documents this resource CITES](#)

Description

This Standard applies to single-phase or polyphase, air-cooled (natural or forced) portable inverters having a rated supply voltage not exceeding 60 V ripple-free d.c. and an alternating current (a.c.) output where the rated output does not exceed 3 kVA; the rated output voltage is within the range 50 500 V a.c.; and the rated frequency of the output is within the range 40 100 Hz.

It is applicable to isolated inverters, equipotentially bonded inverters and RCD protected inverters for household and similar use, use on construction sites, or providing an independent supply to electrical installations in buildings, vehicles, caravans, boats and the like. Inverters may be fitted with terminals for the connection of d.c. supply, an external flexible cord fitted with battery clips, an automobile cigarette lighter plug or other d.c. plug.

[View on Information Provider website](#)

[AS/NZS 4763\(Int\):2006 Safety of portable inverters](#)

Description

This Standard applies to single-phase or polyphase, air-cooled (natural or forced) portable inverters having a rated supply voltage not exceeding 60 V ripple-free d.c. and an alternating current (a.c.) output where the rated output does not exceed 3 kVA; the rated output voltage is within the range 50 500 V a.c.; and the rated frequency of the output is within the range 40 100 Hz.

It is applicable to isolated inverters, equipotentially bonded inverters and RCD protected inverters for household and similar use, use on construction sites, or providing an independent supply to electrical installations in buildings, vehicles, caravans, boats

and the like. Inverters may be fitted with terminals for the connection of d.c. supply, an external flexible cord fitted with battery clips, an automobile cigarette lighter plug or other d.c. plug.

[View on Information Provider website](#)

This resource does not cite any other resources.

AS/NZS 4763(Int):2006 Safety of portable inverters

This resource does not CITE any other resources.

Back

Close

Table of Contents

1 Scope

2 Normative References

3 Definitions

4 General Requirements

5 General Notes on Tests

6 Classification

7 Marking and Other Information

8 Protection against Accessibility to Hazardous Live Parts

9 Output Voltage And Output Current

10 Heating

11 Short Circuit And Overload Protection

12 Mechanical Strength

13 Protection against Harmful Ingress of Dust, Solid Objects and Moisture

14 Insulation Resistance And Dielectric Strength

15 Construction

16 Components

17 Internal Wiring

18 Supply Connections and Other External Flexible Cords

19 Terminals for External Conductors

20 Screws and Connections

21 Creepage Distances, Clearances and Distances through Insulation

22 Resistance to Heat and Fire

23 Resistance to Rusting

Annexes

Annex A (Normative) Measuring Network For Clause 8.2

Annex B (Normative) Requirements For Switches Complying With IEC 61058

Annex C (Normative) Measurement Of Creepage Distances And Clearances

Annex D (Normative) Needle Flame Test

Annex E (Normative) Coated Printed Circuit Board

Annex F (Informative) Verification Of Inverter Separation And RCD Operation

Figures

Figure 1 – Diagrams For Different Types Of Inverter

Figure 2 – Standard Test Finger (See IEC 61032 Test Probe B

Figure 3 – Test Pin (IEC 61032 Test Probe 13)

Figure 4 – Example Of An Electronic Circuit With Low-Power Points (See 11.8)

Figure 5 – Abrasion Resistance Test For Insulating Coated Layers

Figure 6 – Flexing Test Apparatus

Figure A.1 – Measuring Network For Clause 8.2

Tables

Table 1 – Values Of Maximum Temperatures In Normal Use

Table 2 – Maximum Values Of Temperatures Under Short-Circuit Or Overload Conditions

Table 3 – Values Of T And K For Fuses

Table 4 – Values Of Insulation Resistance

Table 5 – Table Of Test Voltages

Table 6 – Nominal Cross-Sectional Areas Of External Flexible Cords

Table 7 – Pull And Torque To Be Applied To External Flexible Cords

Table 8 – Torque To Be Applied To Screws And Connections

Table 9 – Torque Test On Glands

Table 10 – Rated Impulse Voltage

Table 11 – Minimum Clearances

Table 12 – Minimum Creepage Distances For Basic Insulation

Table 13 – Minimum Creepage Distances For Functional Insulation

Table B.1

Bibliography

[Save](#)

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)