

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

  

[Resource detail](#)  
[Citations](#)

## AS/NZS 60898.2:2004 (R2016) Electrical accessories - Circuit-breakers for overcurrent protection for household and similar installations - Part 2: Circuit-breakers for a.c. and d.c. operation

[View on Information Provider website](#)

### Abbreviation

AS/NZS 60898.2:2004

### Valid from

12/08/2004

---

### Information provider

Standards New Zealand

### Author

Standards New Zealand, Standards Australia

### Information type

New Zealand Standard

### Format

PDF

---

### Cited By

[This resource is cited by 1 document \(show Citations\)](#)

---

### Description

This Standard provides essential safety and associated requirements for single-pole and two-pole circuit-breakers, suitable for operation with direct current, with a rated d.c. voltage not exceeding 220 V for single-pole and 440 V for two-pole circuit-breakers, a rated current not exceeding 125 A and a rated d.c. short-circuit capacity not exceeding 10,000 A. Annex ZZ lists variations for Australian and New Zealand conditions.

This Standard is a modified adoption of IEC 60898-2:2003 and should be read in conjunction AS/NZS 60898.1:2004.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

**AS/NZS 60898.2:2004 (R2016) Electrical accessories - Circuit-breakers for**

# overcurrent protection for household and similar installations - Part 2: Circuit-breakers for a.c. and d.c. operation

This document is CITED BY:

- [AS/NZS 3000:2007](#)

AS/NZS 60898.2:2004 is cited by AS/NZS 3000:2007 Electrical installations (known as the Australian/New Zealand Wiring Rules)

Back

## AS/NZS 60898.2:2004 (R2016) Electrical accessories - Circuit-breakers for overcurrent protection for household and similar installations - Part 2: Circuit-breakers for a.c. and d.c. operation

Show what documents this resource is CITED BY

Show what documents this resource CITES

### Description

This Standard provides essential safety and associated requirements for single-pole and two-pole circuit-breakers, suitable for operation with direct current, with a rated d.c. voltage not exceeding 220 V for single-pole and 440 V for two-pole circuit-breakers, a rated current not exceeding 125 A and a rated d.c. short-circuit capacity not exceeding 10,000 A. Annex ZZ lists variations for Australian and New Zealand conditions.

This Standard is a modified adoption of IEC 60898-2:2003 and should be read in conjunction AS/NZS 60898.1:2004.

[View on Information Provider website](#)

[AS/NZS 60898.2:2004 \(R2016\) Electrical accessories - Circuit-breakers for overcurrent protection for household and similar installations - Part 2: Circuit-breakers for a.c. and d.c. operation](#)

### Description

This Standard provides essential safety and associated requirements for single-pole and two-pole circuit-breakers, suitable for operation with direct current, with a rated d.c. voltage not exceeding 220 V for single-pole and 440 V for two-pole circuit-breakers, a rated current not exceeding 125 A and a rated d.c. short-circuit capacity not exceeding 10,000 A. Annex ZZ lists variations for Australian and New Zealand conditions.

This Standard is a modified adoption of IEC 60898-2:2003 and should be read in conjunction AS/NZS 60898.1:2004.

[View on Information Provider website](#)

This resource does not cite any other resources.

## AS/NZS 60898.2:2004 (R2016) Electrical accessories - Circuit-breakers for overcurrent protection for household and similar installations - Part 2: Circuit-breakers for a.c. and d.c. operation

This resource does not CITE any other resources.

Back

Close

Table of Contents

# 1 Scope And Object

# 2 Normative References

# 3 Definitions

# 4 Classification

# 5 Characteristics Of Circuit-Breakers

# 6 Marking And Other Product Information

# 7 Standard Conditions For Operation In Service

# 8 Requirements For Construction And Operation

# 9 Tests

# Annex C

# Figures and Tables

## Figure 7b – Calibration Of The Test Circuit In Case Of Direct Currents

## Figure 18 – Examples Of Connections Of The Circuit-Breakers In Different D.C. Systems

## Table 1 – Preferred Values Of Rated Voltage

## Table 2 – Ranges Of Instantaneous Tripping

## Table 7 – Time-Current Operating Characteristics

## Table C.1 – Test Sequences

## Table C.2 – Number Of Samples For Full Test Procedure

[Save](#)

[Feedback](#)

<input type="text"/>		
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>		

[Feedback](#)