

- [Home Home](#)
- [About this portal](#)
- [Latest updates](#)

[Save](#)

[Resource detail](#)
[Citations](#)

ASTM B335-83A STANDARD SPECIFICATION FOR NICKEL-MOLYBDENUM ALLOY ROD

[View on Information Provider website](#)

Abbreviation

ASTM B335-83A

Version

Revision 83A

Valid from

29/07/1983

Information provider

IHS Markit

Author

American Society of Testing and Materials

Information type

ASTM Standard

Format

PDF, Hard copy

Cited By

[This resource is cited by 1 document \(show Citations\)](#)

Description

This specification covers rod of nickel-molybdenum alloys (UNS N10001, N10665, N10675, N10629, and N10624), for use in general corrosive service.

The following products are covered under this specification:

- Rods $\frac{5}{16}$ to $\frac{3}{4}$ in. (7.94 to 19.05 mm) excl in diameter, hot or cold finished, solution annealed and pickled or mechanically descaled.
- Rods $\frac{3}{4}$ to $3\frac{1}{2}$ in. (19.05 to 88.9 mm) incl in diameter, hot or cold finished, solution annealed, ground or turned.

For assistance with locating previous versions, please contact the information provider.

[View on Information Provider website](#)

For assistance with locating previous versions, please contact the information provider.

This resource is cited by:

ASTM B335-83A STANDARD SPECIFICATION FOR NICKEL-MOLYBDENUM ALLOY ROD

This document is CITED BY:

- [ANSI/ASME B16.5: 1988](#)

ASTM B335-83A is cited by ANSI/ASME B16.5: 1988 Pipe flanges and flanged fittings, steel-nickel alloy and other special alloys

Back

ASTM B335-83A STANDARD SPECIFICATION FOR NICKEL-MOLYBDENUM ALLOY ROD

Show what documents this resource is CITED BY

Show what documents this resource CITES

Description

This specification covers rod of nickel-molybdenum alloys (UNS N10001, N10665, N10675, N10629, and N10624), for use in general corrosive service.

The following products are covered under this specification:

- Rods $\frac{5}{16}$ to $\frac{3}{4}$ in. (7.94 to 19.05 mm) excl in diameter, hot or cold finished, solution annealed and pickled or mechanically descaled.
- Rods $\frac{3}{4}$ to $3\frac{1}{2}$ in. (19.05 to 88.9 mm) incl in diameter, hot or cold finished, solution annealed, ground or turned.

[View on Information Provider website](#)

[ASTM B335-83A STANDARD SPECIFICATION FOR NICKEL-MOLYBDENUM ALLOY ROD](#)

Description

This specification covers rod of nickel-molybdenum alloys (UNS N10001, N10665, N10675, N10629, and N10624), for use in general corrosive service.

The following products are covered under this specification:

- Rods $\frac{5}{16}$ to $\frac{3}{4}$ in. (7.94 to 19.05 mm) excl in diameter, hot or cold finished, solution annealed and pickled or mechanically descaled.
- Rods $\frac{3}{4}$ to $3\frac{1}{2}$ in. (19.05 to 88.9 mm) incl in diameter, hot or cold finished, solution annealed, ground or turned.

[View on Information Provider website](#)

This resource does not cite any other resources.

ASTM B335-83A STANDARD SPECIFICATION FOR NICKEL-MOLYBDENUM ALLOY ROD

This resource does not CITE any other resources.

Back

Close

Table of Contents

Print Save Email

[Feedback](#)

- [Contact us](#)
- [Privacy policy](#)
- [Disclaimer](#)
- [Copyright](#)

[Feedback](#)